



# VITEX S.A.

## CHASSIS - COAT

Revision nr.8  
Dated 16/12/2020  
Printed on 22/07/2022  
Page n. 1 / 15  
Replaced revision:7 (Dated 29/05/2020)

EN

## Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name **CHASSIS - COAT**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Solvent based enamel for metallic surfaces**

#### 1.3. Details of the supplier of the safety data sheet

Name **VITEX S.A.**  
Full address **IMEROS TOPOS**  
District and Country **19300 ASPROPYRGOS (ATTIKI)**  
**GREECE**  
Tel. **(0030) 2105589400**  
Fax **(0030) 2105597859**

e-mail address of the competent person responsible for the Safety Data Sheet **vitexlab@vitex.gr**

Supplier: **VITEX S.A**

#### 1.4. Emergency telephone number

For urgent inquiries refer to **(0030) 2105589400**  
**(0030) 2107793777**

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Warning**

Hazard statements:  
**H226** Flammable liquid and vapour.  
**H319** Causes serious eye irritation.



# VITEX S.A.

## CHASSIS - COAT

Revision nr.8  
Dated 16/12/2020  
Printed on 22/07/2022  
Page n. 2 / 15  
Replaced revision:7 (Dated 29/05/2020)

EN

### SECTION 2. Hazards identification ... / >>

<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH210</b>	Safety data sheet available on request.
<b>EUH211</b>	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
<b>EUH208</b>	Contains: COBALT BIS (2-ETHYLHEXANOATE) May produce an allergic reaction.

#### Precautionary statements:

<b>P101</b>	If medical advice is needed, have product container or label at hand.
<b>P102</b>	Keep out of reach of children.
<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P271</b>	Use only outdoors or in a well-ventilated area.
<b>P405</b>	Store locked up.
<b>P501</b>	Dispose of contents / container in accordance with local and national regulations.
<b>P264</b>	Wash . . . thoroughly after handling.

**Contains:** HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS  
XYLENE (MIXTURE OF ISOMERS)  
HYDROCARBONS, C9, AROMATICS

#### VOC (Directive 2004/42/EC):

One - pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition : 495,00

Limit value: 500,00

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

### SECTION 3. Composition/information on ingredients

#### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, &lt;2% AROMATICS</b>		
CAS	64742-48-9	25 $\leq$ x < 30
EC	919-857-5	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066
<b>INDEX</b>		
REACH Reg. 01-2119463258-33-XXXX		
<b>XYLENE (MIXTURE OF ISOMERS)</b>		
CAS	1330-20-7	9 $\leq$ x < 10
		Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C STA Dermal: 1100 mg/kg, LC50 Inhalation vapours: >10 mg/l/4h
EC	215-535-7	
INDEX	601-022-00-9	
REACH Reg. 01-2119488216-XXXX		
<b>HYDROCARBONS, C9, AROMATICS</b>		
CAS	64742-95-6	6 $\leq$ x < 7
		Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066
EC	918-668-5	
INDEX		
REACH Reg. 01-2119455851-35-XXXX		
<b>Reaction mass of ethylbenzene and m-xylene and p-xylene</b>		
CAS		4 $\leq$ x < 5
		Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C STA Dermal: 1100 mg/kg, LC50 Inhalation vapours: >10 mg/l/4h
EC	905-562-9	



# VITEX S.A.

## CHASSIS - COAT

Revision nr.8  
Dated 16/12/2020  
Printed on 22/07/2022  
Page n. 3 / 15  
Replaced revision:7 (Dated 29/05/2020)

EN

### SECTION 3. Composition/information on ingredients ... / >>

#### INDEX

REACH Reg. 01-2119488216-32-XXXX

#### TRIZINC BIS (ORTHOPHOSPHATE)

CAS 7779-90-0  $1,5 \leq x < 1,55$

Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 231-944-3

INDEX 030-011-00-6

#### HYDROCARBONS, C9-C12, n-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

CAS 64742-82-1  $0 \leq x < 0,3$

Flam. Liq. 3 H226, STOT RE 1 H372, Asp. Tox. 1 H304, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066

EC 919-446-0

#### INDEX

REACH Reg. 01-2119458049-XXXX

#### COBALT BIS (2-ETHYLHEXANOATE)

CAS 136-52-7  $0 \leq x < 0,2$

Repr. 1B H360F, Eye Irrit. 2 H319, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 3 H412

EC 205-250-6

#### INDEX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### SECTION 4. First aid measures

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

### SECTION 5. Firefighting measures

#### 5.1. Extinguishing media

##### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

##### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

#### 5.2. Special hazards arising from the substance or mixture

##### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

#### 5.3. Advice for firefighters

##### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

##### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).



# VITEX S.A.

## CHASSIS - COAT

Revision nr.8  
Dated 16/12/2020  
Printed on 22/07/2022  
Page n. 4 / 15  
Replaced revision:7 (Dated 29/05/2020)

EN

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

Regulatory References:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa



# VITEX S.A.

## CHASSIS - COAT

Revision nr.8  
Dated 16/12/2020  
Printed on 22/07/2022  
Page n. 5 / 15  
Replaced revision:7 (Dated 29/05/2020)

EN

### SECTION 8. Exposure controls/personal protection ... / >>

GBR	United Kingdom	nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
EU	OEL EU	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
		Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

#### HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
MAK	DEU	300	50	600	100			
OEL	EU	1200						
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers			Chronic	Chronic	Effects on workers		
	Acute	Acute				Acute local	Acute	Chronic
	local	systemic	local	systemic		systemic	local	systemic
Oral			VND	300				
				mg/kg/d				
Inhalation			VND	900	VND	1500		
				mg/m3		mg/m3		
Skin			VND	300			VND	300
				ma/ka/d				ma/ka/d

#### XYLENE (MIXTURE OF ISOMERS)

Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	221		442		SKIN		
TLV	CZE	200		400		SKIN		
AGW	DEU	440	100	880	200	SKIN		
MAK	DEU	440	100	880	200	SKIN		
VLEP	FRA	221	50	442	100	SKIN		
TLV	GRC	435	100	650	150	SKIN		
AK	HUN	221		442		SKIN		
GVI/KGVI	HRV	221	50	442	100	SKIN		
NPEL	SVK	221	50	442		SKIN		
WEL	GBR	220	50	441	100			
OEL	EU	221	50	442	100	SKIN		
TLV-ACGIH		434	100	651	150			
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d



# VITEX S.A.

## CHASSIS - COAT

Revision nr.8  
Dated 16/12/2020  
Printed on 22/07/2022  
Page n. 6 / 15  
Replaced revision:7 (Dated 29/05/2020)

EN

### SECTION 8. Exposure controls/personal protection ... / >>

#### HYDROCARBONS, C9, AROMATICS

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
OEL	EU	100						

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	11 mg/kg/d				
Inhalation			VND	150 mg/m3			VND	32 mg/m3
Skin			VND	11 mg/kg/d			VND	25 mg/kg/d

#### Reaction mass of ethylbenzene and m-xylene and p-xylene

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	221		442		SKIN		
TLV	CZE	200		400		SKIN		
AGW	DEU	440	100	880	200	SKIN		
MAK	DEU	440	100	880	200	SKIN		
VLEP	FRA	221	50	442	100	SKIN		
TLV	GRC	435	100	650	150	SKIN		
AK	HUN	221		442		SKIN		
GVI/KGVI	HRV	221	50	442	100	SKIN		
NPEL	SVK	221	50	442		SKIN		
WEL	GBR	220	50	441	100			
OEL	EU	221	50	442	100	SKIN		
TLV-ACGIH		434	100	651	150			

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

#### HYDROCARBONS, C9-C12, n-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
OEL	EU	350						

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	26 mg/kg/d				
Inhalation			VND	71 mg/m3			VND	330 mg/m3
Skin			VND	26 mg/kg/d			VND	44 mg/kg/d



# VITEX S.A.

## CHASSIS - COAT

Revision nr.8  
Dated 16/12/2020  
Printed on 22/07/2022  
Page n. 7 / 15  
Replaced revision:7 (Dated 29/05/2020)

EN

### SECTION 8. Exposure controls/personal protection ... / >>

#### COBALT BIS (2-ETHYLHEXANOATE)

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
TLV	GRC	5							
Health - Derived no-effect level - DNEL / DMEL									
	Effects on consumers				Effects on workers				
Route of exposure	Acute	Acute		Chronic	Chronic	Acute local	Acute	Chronic	Chronic
	local	systemic		local	systemic		systemic	local	systemic
Oral					0,0095				
					mg/kg bw/d				
Inhalation					0,0063		0,235		
					mg/m3		mg/m3		
Skin		NPI							

##### Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

##### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

##### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

##### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

##### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

##### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

### SECTION 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	viscous liquid	
Colour	as showed in color folder	
Odour	characteristic	
Melting point / freezing point	Not available	
Initial boiling point	Not available	
Flammability	Not available	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Flash point	23 ≤ T ≤ 60	°C
Auto-ignition temperature	Not available	
pH		



# VITEX S.A.

## CHASSIS - COAT

Revision nr.8  
Dated 16/12/2020  
Printed on 22/07/2022  
Page n. 8 / 15  
Replaced revision:7 (Dated 29/05/2020)

EN

### SECTION 9. Physical and chemical properties ... / >>

Kinematic viscosity	Not available	
Dynamic viscosity	Not available	
	75-85 KU	Method:ASTM D 562
		Temperature: = 25 °C
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	Not available	
Vapour pressure	Not available	
Density and/or relative density	1,33-1,37 kg/l	Method:ISO 2811
Relative vapour density	Not available	
Particle characteristics	Not applicable	

#### 9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

### SECTION 10. Stability and reactivity

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

#### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

#### 10.5. Incompatible materials

Information not available

#### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

### SECTION 11. Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture: > 20 mg/l





# VITEX S.A.

## CHASSIS - COAT

Revision nr.8  
Dated 16/12/2020  
Printed on 22/07/2022  
Page n. 9 / 15  
Replaced revision:7 (Dated 29/05/2020)

EN

### SECTION 11. Toxicological information ... / >>

ATE (Oral) of the mixture:  
ATE (Dermal) of the mixture:

Not classified (no significant component)  
>2000 mg/kg

HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

LD50 (Dermal): > 5000 mg/kg Rabbit  
LD50 (Oral): > 5000 mg/kg Rat  
LC50 (Inhalation vapours): > 20 mg/l/4h Rat

XYLENE (MIXTURE OF ISOMERS)

STA (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)  
LD50 (Oral): > 2000 mg/kg Rat  
LC50 (Inhalation vapours): > 10 mg/l/4h Rat

HYDROCARBONS, C9, AROMATICS

LD50 (Dermal): > 2000 mg/kg Rabbit  
LD50 (Oral): > 2000 mg/kg Rat  
LC50 (Inhalation vapours): > 20 mg/l/4h

Reaction mass of ethylbenzene and m-xylene and p-xylene

STA (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)  
LD50 (Oral): > 2000 mg/kg Rat  
LC50 (Inhalation vapours): > 10 mg/l/4h Rat

TRIZINC BIS (ORTHOPHOSPHATE)

LD50 (Oral): > 5000 mg/kg Rat - Wistar  
LC50 (Inhalation mists/powders): > 5,7 mg/l Rat

HYDROCARBONS, C9-C12, n-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

LD50 (Oral): > 5000 mg/kg Rat  
LC50 (Inhalation vapours): > 20 mg/l/4h Rat

#### SKIN CORROSION / IRRITATION

Causes skin irritation

#### SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

#### RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

COBALT BIS (2-ETHYLHEXANOATE)

#### Respiratory sensitization

Information not available

#### Skin sensitization

Information not available

#### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### Adverse effects on sexual function and fertility



# VITEX S.A.

## CHASSIS - COAT

Revision nr.8  
Dated 16/12/2020  
Printed on 22/07/2022  
Page n. 10 / 15  
Replaced revision:7 (Dated 29/05/2020)

EN

### SECTION 11. Toxicological information ... / >>

Information not available

#### Adverse effects on development of the offspring

Information not available

#### Effects on or via lactation

Information not available

#### STOT - SINGLE EXPOSURE

May cause respiratory irritation  
May cause drowsiness or dizziness

#### Target organs

Information not available

#### Route of exposure

Information not available

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### Target organs

Information not available

#### Route of exposure

Information not available

#### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

### SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

### 12.1. Toxicity

Reaction mass of ethylbenzene and m-xylene and p-xylene

LC50 - for Fish	> 1 mg/l/96h
EC50 - for Crustacea	> 1 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 1 mg/l/72h
Chronic NOEC for Fish	> 1 mg/l based on test data
Chronic NOEC for Crustacea	> 0,1 mg/l

COBALT BIS (2-ETHYLHEXANOATE)

LC50 - for Fish	275 mg/l/96h
EC50 - for Algae / Aquatic Plants	654,2 mg/l/72h

XYLENE (MIXTURE OF ISOMERS)

LC50 - for Fish	> 1 mg/l/96h
EC50 - for Crustacea	> 1 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 1 mg/l/72h
Chronic NOEC for Fish	> 1 mg/l based on test data
Chronic NOEC for Crustacea	> 0,1 mg/l



# VITEX S.A.

## CHASSIS - COAT

Revision nr.8  
Dated 16/12/2020  
Printed on 22/07/2022  
Page n. 11 / 15  
Replaced revision:7 (Dated 29/05/2020)

EN

### SECTION 12. Ecological information ... / >>

HYDROCARBONS, C9-C12, n-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)  
LC50 - for Fish > 1 mg/l/96h  
EC50 - for Crustacea > 1 mg/l/48h  
EC50 - for Algae / Aquatic Plants > 1 mg/l/72h  
Chronic NOEC for Fish > 0,1 mg/l based on modeled data  
Chronic NOEC for Crustacea > 0,1 mg/l based on test data

HYDROCARBONS, C9, AROMATICS  
LC50 - for Fish > 1 mg/l/96h  
EC50 - for Crustacea > 1 mg/l/48h  
EC50 - for Algae / Aquatic Plants > 1 mg/l/72h  
Chronic NOEC for Fish > 1 mg/l based on modeled data  
Chronic NOEC for Crustacea > 1 mg/l based on modeled data

HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS  
LC50 - for Fish > 100 mg/l/96h  
EC50 - for Crustacea > 100 mg/l/48h  
EC50 - for Algae / Aquatic Plants > 100 mg/l/72h  
Chronic NOEC for Fish > 0,1 mg/l based on modeled data  
Chronic NOEC for Crustacea > 0,1 mg/l based on modeled data

TRIZINC BIS (ORTHOPHOSPHATE)  
LC50 - for Fish 0,78 mg/l/96h Pimephales promelas  
EC50 - for Crustacea 0,86 mg/l/48h Daphnia magna

#### 12.2. Persistence and degradability

Reaction mass of ethylbenzene and m-xylene and p-xylene  
Rapidly degradable

COBALT BIS (2-ETHYLHEXANOATE)  
Entirely degradable

XYLENE (MIXTURE OF ISOMERS)  
Rapidly degradable

HYDROCARBONS, C9-C12, n-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)  
Rapidly degradable

HYDROCARBONS, C9, AROMATICS  
Rapidly degradable

HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS  
Rapidly degradable

TRIZINC BIS (ORTHOPHOSPHATE)  
Solubility in water 2,7 mg/l  
Degradability: information not available

#### 12.3. Bioaccumulative potential

Reaction mass of ethylbenzene and m-xylene and p-xylene  
Partition coefficient: n-octanol/water 3,12

XYLENE (MIXTURE OF ISOMERS)  
Partition coefficient: n-octanol/water 3,12

HYDROCARBONS, C9-C12, n-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)  
Partition coefficient: n-octanol/water 3,7

HYDROCARBONS, C9, AROMATICS  
Partition coefficient: n-octanol/water 3,7

HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS  
Partition coefficient: n-octanol/water 5

#### 12.4. Mobility in soil



# VITEX S.A.

## CHASSIS - COAT

Revision nr.8  
Dated 16/12/2020  
Printed on 22/07/2022  
Page n. 12 / 15  
Replaced revision:7 (Dated 29/05/2020)

EN

### SECTION 12. Ecological information ... / >>

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

#### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

### SECTION 13. Disposal considerations

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### SECTION 14. Transport information

#### 14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1263

The product, if packaged in packages of less than 450 litres, is not subject to ADR regulations as stated in 2.2.3.1.5.

The product, if packaged in packages of less than 450 litres, is not subject to obligations relating to marking, labelling and package testing in accordance with 2.3.2.5 of the IMDG CODE.

#### 14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

#### 14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



#### 14.4. Packing group

ADR / RID, IMDG, IATA: III

#### 14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO



# VITEX S.A.

## CHASSIS - COAT

Revision nr.8  
Dated 16/12/2020  
Printed on 22/07/2022  
Page n. 13 / 15  
Replaced revision:7 (Dated 29/05/2020)

EN

### SECTION 14. Transport information ... / >>

#### 14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30 Special provision: 163, 367, 650	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Pass.:	Maximum quantity: 60 L	Packaging instructions: 355
	Special provision:	A3, A72, A192	

#### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

### SECTION 15. Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC):

One - pack performance coatings.

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

### SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Repr. 1B</b>	Reproductive toxicity, category 1B
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>STOT RE 1</b>	Specific target organ toxicity - repeated exposure, category 1
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Aquatic Acute 1</b>	Hazardous to the aquatic environment, acute toxicity, category 1



# VITEX S.A.

## CHASSIS - COAT

Revision nr.8  
Dated 16/12/2020  
Printed on 22/07/2022  
Page n. 14 / 15  
Replaced revision:7 (Dated 29/05/2020)

EN

### SECTION 16. Other information ... / >>

<b>Aquatic Chronic 1</b>	Hazardous to the aquatic environment, chronic toxicity, category 1
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H226</b>	Flammable liquid and vapour.
<b>H360F</b>	May damage fertility.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H372</b>	Causes damage to organs through prolonged or repeated exposure.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H400</b>	Very toxic to aquatic life.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH210</b>	Safety data sheet available on request.
<b>EUH211</b>	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148



# VITEX S.A.

## CHASSIS - COAT

Revision nr.8  
Dated 16/12/2020  
Printed on 22/07/2022  
Page n. 15 / 15  
Replaced revision:7 (Dated 29/05/2020)

EN

### SECTION 16. Other information ... / >>

18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

02 / 03.