



VITEX S.A.

DIAXYL EXTRA

Revision nr.7
Dated 16/11/2023
Printed on 16/11/2023
Page n. 1 / 12
Replaced revision:6 (Dated 23/03/2023)

EN

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **DIAXYL EXTRA**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Solvent based wood preservative for exterior use.**

1.3. Details of the supplier of the safety data sheet

Name **VITEX S.A.**
Full address **IMEROS TOPOS**
District and Country **19300 ASPROPYRGOS (ATTIKI)**
GREECE
Tel. **(0030) 2105589400**
Fax **(0030) 2105597859**

e-mail address of the competent person responsible for the Safety Data Sheet **vitexlab@vitex.gr**

Supplier: **VITEX S.A**

1.4. Emergency telephone number

For urgent inquiries refer to **(0030) 2105589400**
(0030) 2107793777 Emergency number Greece 24/7
1401 Cyprus

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye irritation, category 2	H319	Causes serious eye irritation.
Hazardous to the aquatic environment, acute toxicity, category 1	H400	Very toxic to aquatic life.
Hazardous to the aquatic environment, chronic toxicity, category 1	H410	Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





VITEX S.A.

DIAXYL EXTRA

Revision nr.7
Dated 16/11/2023
Printed on 16/11/2023
Page n. 2 / 12
Replaced revision:6 (Dated 23/03/2023)

EN

SECTION 2. Hazards identification ... / >>

Signal words: Danger

Hazard statements:

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H410 Very toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH208 Contains: PROPICONAZOLE
PERMETHRIN (ISO)
3-IODO-2-PROPYNILBUTYL CARBAMATE
POLY(ETHYLENE GLYCOL) DIMETHACRYLATE
May produce an allergic reaction.

Precautionary statements:

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER / doctor / . . .
P370+P378 In case of fire: use [. . .] to extinguish.
P280 Wear protective gloves / protective clothing / eye protection / face protection / hearing protection.
P501 Dispose of contents / container in accordance with local and national regulations.
P102 Keep out of reach of children.
P101 If medical advice is needed, have product container or label at hand.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331 Do NOT induce vomiting.
P403+P235 Store in a well-ventilated place. Keep cool.
P273 Avoid release to the environment.
P405 Store locked up.
P264 Wash . . . thoroughly after handling.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P391 Collect spillage.

Contains: HYDROCARBONS, C10-C13, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

VOC (Directive 2004/42/EC) :

Binding primers.

VOC given in g/litre of product in a ready-to-use condition : 749,00

Limit value: 750,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
HYDROCARBONS, C10-C13, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS		
INDEX	75 \leq x < 85	Asp. Tox. 1 H304, EUH066
EC	918-481-9	
CAS	64742-48-9	
REACH Reg.	01-2119457273-XXXX	
2-BUTOXYETHANOL		
INDEX	603-014-00-0	Acute Tox. 3 H331, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC	203-905-0	LD50 Oral: 1200 mg/kg, LC50 Inhalation vapours: 3 mg/l/4h
CAS	111-76-2	



VITEX S.A.

DIAXYL EXTRA

Revision nr.7
Dated 16/11/2023
Printed on 16/11/2023
Page n. 3 / 12
Replaced revision:6 (Dated 23/03/2023)

EN

SECTION 3. Composition/information on ingredients ... / >>

Oxirane, 2-methyl-, polymer with oxirane, mono(2-ethylhexyl) ether

INDEX $2 \leq x < 4$ Acute Tox. 4 H332, Aquatic Chronic 3 H412
EC STA Inhalation vapours: 11 mg/l

CAS 64366-70-7

Paraffin oil

INDEX $0,5 \leq x < 1,5$ Asp. Tox. 1 H304

EC 232-455-8

CAS 8042-47-5

POLY(ETHYLENE GLYCOL) DIMETHACRYLATE

INDEX $0,8 \leq x < 1$ Skin Sens. 1 H317

EC

CAS 26142-30-3

3-IODO-2-PROPYNYLBUTYL CARBAMATE

INDEX 616-212-00-7 $0,74 \leq x < 0,76$ Acute Tox. 3 H331, Acute Tox. 4 H302, STOT RE 1 H372, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=1
LD50 Oral: 1056 mg/kg, STA Inhalation vapours: 3 mg/l, STA Inhalation mists/powders: 0,501 mg/l

EC 259-627-5

CAS 55406-53-6

PERMETHRIN (ISO)

INDEX 613-058-00-2 $0,24 \leq x < 0,26$ Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1000, Aquatic Chronic 1 H410 M=1000
STA Oral: 500 mg/kg, STA Inhalation vapours: 11 mg/l

EC 258-067-9

CAS 52645-53-1

PROPICONAZOLE

INDEX 613-205-00-0 $0,23 \leq x < 0,25$ Repr. 1B H360D, Acute Tox. 4 H302, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
LD50 Oral: 1517 mg/kg

EC 262-104-4

CAS 60207-90-1

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE



VITEX S.A.

DIAXYL EXTRA

Revision nr.7
Dated 16/11/2023
Printed on 16/11/2023
Page n. 4 / 12
Replaced revision:6 (Dated 23/03/2023)

EN

SECTION 5. Firefighting measures ... / >>

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition.

7.3. Specific end use(s)

Information not available



VITEX S.A.

DIAXYL EXTRA

Revision nr.7
Dated 16/11/2023
Printed on 16/11/2023
Page n. 5 / 12
Replaced revision:6 (Dated 23/03/2023)

EN

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

HYDROCARBONS, C10-C13, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU	300	50	600	100	
OEL	EU	1200				

2-BUTOXYETHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	98	20	246	50	SKIN
TLV-ACGIH		97	20			

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.



VITEX S.A.

DIAXYL EXTRA

Revision nr.7
Dated 16/11/2023
Printed on 16/11/2023
Page n. 6 / 12
Replaced revision:6 (Dated 23/03/2023)

EN

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	colourless	
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	57,5 °C	Method:Closed Cup Pensky-Martens
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	
Kinematic viscosity	0,014 cm ² /s	Temperature: = 40 °C
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	0,79-0,83 kg/l	Method:ISO 2811
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Explosive properties	not applicable
Oxidising properties	not applicable

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-BUTOXYETHANOL

Decomposes under the effect of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

2-BUTOXYETHANOL

May react dangerously with: aluminium,oxidising agents.Forms peroxides with: air.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.



VITEX S.A.

DIAXYL EXTRA

Revision nr.7
Dated 16/11/2023
Printed on 16/11/2023
Page n. 7 / 12
Replaced revision:6 (Dated 23/03/2023)

EN

SECTION 10. Stability and reactivity ... / >>

2-BUTOXYETHANOL

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

2-BUTOXYETHANOL

May develop: hydrogen.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	Not classified (no significant component)

HYDROCARBONS, C10-C13, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

LD50 (Dermal):	> 5000 mg/kg
LD50 (Oral):	> 5000 mg/kg
LC50 (Inhalation vapours):	> 20 mg/l/4h Rat

2-BUTOXYETHANOL

LD50 (Oral):	1200 mg/kg Guinea pig
LC50 (Inhalation vapours):	3 mg/l/4h Rat

Oxirane, 2-methyl-, polymer with oxirane, mono(2-ethylhexyl) ether

LD50 (Dermal):	> 4000 mg/kg Rat
LD50 (Oral):	2645 mg/kg Rat
LC50 (Inhalation vapours):	2,76 mg/l/4h Rat
STA (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

3-IODO-2-PROPYNYLBUTYLCARBAMATE

LD50 (Dermal):	> 2000 mg/kg Rabbit
LD50 (Oral):	1056 mg/kg Rat

PERMETHRIN (ISO)

LC50 (Inhalation vapours):	> 2,65 mg/l/4h Rat
----------------------------	--------------------

PROPICONAZOLE

LD50 (Dermal):	> 4 mg/kg Rat
LD50 (Oral):	1517 mg/kg Rat
LC50 (Inhalation vapours):	1264 mg/l/4h Rat



VITEX S.A.

DIAXYL EXTRA

Revision nr.7
Dated 16/11/2023
Printed on 16/11/2023
Page n. 8 / 12
Replaced revision:6 (Dated 23/03/2023)

EN

SECTION 11. Toxicological information ... / >>

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

PROPICONAZOLE

PERMETHRIN (ISO)

3-IODO-2-PROPYNYLBUTYLCARBAMATE

POLY(ETHYLENE GLYCOL) DIMETHACRYLATE

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

3-IODO-2-PROPYNYLBUTYLCARBAMATE

LC50 - for Fish 0,067 mg/l/96h

EC50 - for Crustacea 0,16 mg/l/48h

EC50 - for Algae / Aquatic Plants 0,022 mg/l/72h

HYDROCARBONS, C10-C13, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

LC50 - for Fish > 100 mg/l/96h

EC50 - for Crustacea > 100 mg/l/48h

EC50 - for Algae / Aquatic Plants > 100 mg/l/72h

Chronic NOEC for Fish > 0,1 mg/l based on modeled data

Chronic NOEC for Crustacea > 0,1 mg/l based on modeled data



VITEX S.A.

DIAXYL EXTRA

Revision nr.7
Dated 16/11/2023
Printed on 16/11/2023
Page n. 9 / 12
Replaced revision:6 (Dated 23/03/2023)

EN

SECTION 12. Ecological information ... / >>

PROPICONAZOLE
LC50 - for Fish 4,3 mg/l/96h
EC50 - for Crustacea 10,2 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants 0,76 mg/l/72h Scenedesmus subspicatus

PERMETHRIN (ISO)
LC50 - for Fish 0,001 mg/l/96h Oncorhynchus clarkii stomias
EC50 - for Crustacea 0,0003 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants 1,6 mg/l/72h Anabaena inaequalis

Oxirane, 2-methyl-, polymer with oxirane, mono(2-ethylhexyl) ether
LC50 - for Fish 20 mg/l/96h Brachydanio rerio

12.2. Persistence and degradability

3-iodo-2-propynylbutylcarbamate
Rapidly degradable

HYDROCARBONS, C10-C13, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS
Rapidly degradable

2-BUTOXYETHANOL
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

PROPICONAZOLE
NOT rapidly degradable

12.3. Bioaccumulative potential

3-iodo-2-propynylbutylcarbamate
Partition coefficient: n-octanol/water 2,81

2-BUTOXYETHANOL
Partition coefficient: n-octanol/water 0,81

PROPICONAZOLE
Partition coefficient: n-octanol/water 3,65 Log Kow

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.



VITEX S.A.

DIAXYL EXTRA

Revision nr.7
Dated 16/11/2023
Printed on 16/11/2023
Page n. 10 / 12
Replaced revision:6 (Dated 23/03/2023)

EN

SECTION 13. Disposal considerations ... / >>

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: UN 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: Environmentally Hazardous

IMDG: Marine Pollutant

IATA: NO



For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30 Special provision: 163, 367, 650	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 L	
IATA:	Cargo: Passengers: Special provision:	Maximum quantity: 220 L Maximum quantity: 60 L A3, A72, A192	Packaging instructions: 366 Packaging instructions: 355

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant



VITEX S.A.

DIAXYL EXTRA

Revision nr.7
Dated 16/11/2023
Printed on 16/11/2023
Page n. 11 / 12
Replaced revision:6 (Dated 23/03/2023)

EN

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c-E1

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:
PERMETHRIN (ISO)

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC):

Binding primers.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Repr. 1B	Reproductive toxicity, category 1B
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H226	Flammable liquid and vapour.
H360D	May damage the unborn child.
H331	Toxic if inhaled.
H302	Harmful if swallowed.



VITEX S.A.

DIAXYL EXTRA

Revision nr.7
Dated 16/11/2023
Printed on 16/11/2023
Page n. 12 / 12
Replaced revision:6 (Dated 23/03/2023)

EN

SECTION 16. Other information ... / >>

H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148



VITEX S.A.

DIAXYL EXTRA

Revision nr.7
Dated 16/11/2023
Printed on 16/11/2023
Page n. 13 / 12
Replaced revision:6 (Dated 23/03/2023)

EN

SECTION 16. Other information ... / >>

18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

02 / 03 / 08 / 11 / 12 / 14 / 15.