



ΕN

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the sub	stance/mi	ixture and of the co	mpany/undertaking
1.1. Product identifier			
Product name	MINIO		
1.2. Relevant identified uses of the substance or r	nixture and u	ses advised against	
Intended use	Anticorrosi	ve primer for metallic surf	aces
1.3. Details of the supplier of the safety data shee	t		
Name Full address District and Country	VITEX S.A. IMEROS TO 19300 Tel. Fax		(ΑΤΤΙΚΙ)
e-mail address of the competent person responsible for the Safety Data Sheet	vitexlab@v	itex.gr	
Supplier:	VITEX S.A		
1.4. Emergency telephone number			
For urgent inquiries refer to	(0030) 2105 (0030) 2107		

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:		
Flammable liquid, category 3	H226	Flammable liquid and vapour.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Warning

Hazard statements: H226 H319 H315

Flammable liquid and vapour. Causes serious eye irritation. Causes skin irritation.



ΕN

SECTION 2. Hazards identification ... / >> H336 May cause drowsiness or dizziness.

H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
Precautionary statemer	nts:
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P405	Store locked up.
P501	Dispose of contents / container in accordance with local and national regulations.
P264	Wash thoroughly after handling.
Contains:	HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

VOC (Directive 2004/42/EC) :	
One - pack performance coatings.	
VOC given in g/litre of product in a ready-to-use condition :	449,00
Limit value:	500,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\ge 0.1\%$.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

```
Contains:
```

Identification		x = Conc. %	Classification (EC) 1272/2008 (CLP)
HYDROCARB	ONS, C9-C11, n-	ALKANES, ISOALKAN	NES, CYCLICS, <2% AROMATICS
CAS EC INDEX	64742-48-9 919-857-5	20 ≤ x < 25	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066
REACH Reg.	01-2119463258	-33-XXXX	
XYLENE (MIX	TURE OF ISOME	ERS)	
CAS	1330-20-7	8≤x< 9	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C
EC	215-535-7		STA Dermal: 1100 mg/kg, LC50 Inhalation vapours: >10 mg/l/4h
INDEX	601-022-00-9		· · ·
REACH Reg.	01-2119488216	-XXXX	
Reaction mas	s of ethylbenzen	ne and m-xylene and p	p-xylene
CAS		5≤x< 6	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304 STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C
EC INDEX	905-562-9		STA Dermal: 1100 mg/kg, LC50 Inhalation vapours: >10 mg/l/4h
REACH Reg.	01-2119488216	-32-XXXX	
Aluminium Di	HydrogenTripho	sphate diHydrate	
CAS	13939-25-8	$3 \le x \le 4$	Eye Irrit. 2 H319
EC INDEX	237-714-9		
REACH Reg.	01-2119970565	-28	
CAS EC	1314-13-2 215-222-5	1,3 ≤ x < 1,4	Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
INDEX REACH Reg.	01-2119466388		





SECTION 3. Composition/information on ingredients/>>

ACETONE

CAS 67-64-1 EC 200-662-2 INDEX 606-001-00-8

0,1 ≤ x < 0,15

Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak. UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations. SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.



SECTION 6. Accidental release measures .../>>

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
FRA GRC	France Ελλάδα	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022



SECTION 8. Exposure controls/personal protection/>>

HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Threshold Limit	t Value								
Туре	Country	/ TWA	/8h	STEL/15	min	Remarks / O	bservations		
		mg/m	n3 ppm	mg/m3	ppm				
MAK	DEU	300	50	600	100				
OEL	EU	1200							
lealth - Derived	I no-effect I	evel - DNI	EL / DMEL						
	E	ffects on c	onsumers			Effects on wor	kers		
Route of expo	osure A	cute	Acute	Chronic	Chronic	Acute local	Acute	Chronic	Chronic
	lo	ocal	systemic	local	systemic		systemic	local	systemic
Oral				VND	300				
					mg/kg/d				
Inhalation				VND	900	VND	1500		
					mg/m3		mg/m3		
Skin				VND	300			VND	300
					mg/kg/d				mg/kg/d

XYLENE (MIXTURE OF ISOMERS)

Threshold Limit	Value								
Туре	Country	TWA/8h		STEL/15	min	Remarks / Ob	servations		
		mg/m3	ppm	mg/m3	ppm				
TLV	BGR	221		442		SKIN			
TLV	CZE	200		400		SKIN			
AGW	DEU	440	100	880	200	SKIN			
MAK	DEU	440	100	880	200	SKIN			
VLEP	FRA	221	50	442	100	SKIN			
TLV	GRC	435	100	650	150	SKIN			
AK	HUN	221		442		SKIN			
GVI/KGVI	HRV	221	50	442	100	SKIN			
NPEL	SVK	221	50	442		SKIN			
WEL	GBR	220	50	441	100				
OEL	EU	221	50	442	100	SKIN			
TLV-ACGIH		434	100	651	150				
Health - Derived	no-effect lev	el - DNEL /	DMEL						
	Effe	ects on consu	umers			Effects on work	ers		
Route of expos	sure Acu	ite Aci	ute	Chronic	Chronic	Acute local	Acute	Chronic	Chronic
	loca	al sys	temic	local	systemic		systemic	local	systemic
Oral				VND	1,6				
					mg/kg/d				
Inhalation	174	174	1	VND	14,8	289	289	VND	77
	mg/	m3 mg	/m3		mg/m3	mg/m3	mg/m3		mg/m3
Skin				VND	108			VND	180
					mg/kg/d				mg/kg/d



ΕN

SECTION 8. Exposure controls/personal protection/>>

Reaction mass of ethylbenzene and m-xylene and p-xylene

Threshold Limit	Value								
Туре	Country	TWA/8	n	STEL/15	min	Remarks / Ob	servations		
		mg/m3	ppm	mg/m3	ppm				
TLV	BGR	221		442		SKIN			
TLV	CZE	200		400		SKIN			
AGW	DEU	440	100	880	200	SKIN			
MAK	DEU	440	100	880	200	SKIN			
VLEP	FRA	221	50	442	100	SKIN			
TLV	GRC	435	100	650	150	SKIN			
AK	HUN	221		442		SKIN			
GVI/KGVI	HRV	221	50	442	100	SKIN			
NPEL	SVK	221	50	442		SKIN			
WEL	GBR	220	50	441	100				
OEL	EU	221	50	442	100	SKIN			
TLV-ACGIH		434	100	651	150				
lealth - Derived	no-effect le	vel - DNEL	/ DMEL						
	Ef	fects on con	sumers			Effects on work	kers		
Route of expos	sure Ac	ute A	cute	Chronic	Chronic	Acute local	Acute	Chronic	Chronic
	loc	cal s	ystemic	local	systemic		systemic	local	systemic
Oral				VND	1,6				
					mg/kg/d				
Inhalation	17	4 1	74	VND	14,8	289	289	VND	77
	m	g/m3 n	ng/m3		mg/m3	mg/m3	mg/m3		mg/m3
Skin				VND	108			VND	180
					mg/kg/d				mg/kg/d

ACETONE Threshold Limit Value TWA/8h STEL/15min Remarks / Observations Туре Country mg/m3 mg/m3 ppm ppm TLV BGR 600 1400 TLV CZE 800 331,2 1500 621 2400 (C) 1000 (C) DEU 500 AGW 1200 1000 MAK DEU 1200 500 2400 VLEP FRA 1210 500 2420 1000 TLV GRC 1780 3560 AK HUN 1210 GVI/KGVI 500 HRV 1210 ROU 500 TLV 1210 NPEL SVK 500 1210 WEL GBR 1210 500 3620 1500 OEL EU 1210 500 TLV-ACGIH 500 250

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion. EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).





ΕN

SECTION 8. Exposure controls/personal protection/>>

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required. Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value		Information
Appearance	viscous liquid		
Colour	orange		
Odour	characteristic of so	olvent	
Melting point / freezing point	not available		
Initial boiling point	not available		
Flammability	not available		
Lower explosive limit	not available		
Upper explosive limit	not available		
Flash point	27 °C		
Auto-ignition temperature	not available		
pH	not available		
Kinematic viscosity	not available		
Dynamic viscosity	75 - 85 KU		Method:ASTM D 562
Solubility	insoluble in water		
Partition coefficient: n-octanol/water	not available		
Vapour pressure	not available		
Density and/or relative density	1,46-1,50 l	kg/l	Method:ISO 2811
Relative vapour density	not available		
Particle characteristics	not applicable		

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ACETONE

Decomposes under the effect of heat.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

ACETONE

Risk of explosion on contact with: bromine trifluoride,fluorine dioxide,hydrogen peroxide,nitrosyl chloride,2-methyl-1,3





Revision nr.6 Dated 25/08/2022 Printed on 01/09/2023 Page n. 8 / 14 Replaced revision:5 (Dated 09/12/2020)

SECTION 10. Stability and reactivity .../>>

butadiene,nitromethane,nitrosyl perchlorate.May react dangerously with: potassium tert-butoxide,alkaline hydroxides,bromine,bromoform,isoprene,sodium,sulphur dioxide,chromium trioxide,chromyl chloride,nitric acid,chloroform,peroxymonosulphuric acid,phosphoryl oxychloride,chromosulphuric acid,fluorine,strong oxidising agents,strong reducing agents.Develops flammable gas on contact with: nitrosyl perchlorate.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ACETONE

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

ACETONE

Incompatible with: acids,oxidising substances.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ACETONE

May develop: ketenes,irritant substances.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	>2000 mg/kg

HYDROCARBONS, C9-C11, n-ALKANES, ISO, LD50 (Dermal): LD50 (Oral): LC50 (Inhalation vapours):	ALKANES, CYCLICS, <2% AROMATICS > 5000 mg/kg Rabbit > 5000 mg/kg Rat > 20 mg/l/4h Rat
XYLENE (MIXTURE OF ISOMERS)	
STA (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP
	(figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	> 2000 mg/kg Rat
LC50 (Inhalation vapours):	> 10 mg/l/4h Rat
Reaction mass of ethylbenzene and m-xylene a	nd p-xylene
STA (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP
	(figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	> 2000 mg/kg Rat
LC50 (Inhalation vapours):	> 10 mg/l/4h Rat





SECTION 11. Toxicological information ... / >>

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

Respiratory sensitization

Information not available

Skin sensitization

Information not available

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation

Information not available

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

Target organs

Information not available

Route of exposure

Information not available

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

ASPIRATION HAZARD



ΕN

SECTION 11. Toxicological information ... / >>

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

Reaction mass of ethylbenzene and m-xylene and p-xyler LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants Chronic NOEC for Fish Chronic NOEC for Crustacea	ne > 1 mg/l/96h > 1 mg/l/48h > 1 mg/l/72h > 1 mg/l based on test data > 0,1 mg/l
XYLENE (MIXTURE OF ISOMERS) LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants Chronic NOEC for Fish Chronic NOEC for Crustacea	> 1 mg/l/96h > 1 mg/l/48h > 1 mg/l/72h > 1 mg/l based on test data > 0,1 mg/l
HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants Chronic NOEC for Fish Chronic NOEC for Crustacea	S, CYCLICS, <2% AROMATICS > 100 mg/l/96h > 100 mg/l/48h > 100 mg/l/72h > 0,1 mg/l based on modeled data > 0,1 mg/l based on modeled data
12.2. Persistence and degradability	
Reaction mass of ethylbenzene and m-xylene and p-xyle Rapidly degradable	ne
XYLENE (MIXTURE OF ISOMERS) Rapidly degradable	
HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES Rapidly degradable	S, CYCLICS, <2% AROMATICS
ACETONE Rapidly degradable	
12.3. Bioaccumulative potential	
Reaction mass of ethylbenzene and m-xylene and p-xyle Partition coefficient: n-octanol/water	ne 3,12
XYLENE (MIXTURE OF ISOMERS) Partition coefficient: n-octanol/water	3,12
HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES Partition coefficient: n-octanol/water	S, CYCLICS, <2% AROMATICS 5
ACETONE Partition coefficient: n-octanol/water BCF	-0,23 3
12.4. Mobility in soil	
Information not available	





ΕN

SECTION 12. Ecological information ... / >>

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1263


14.2. UN proper shipping name

PAINT or PAINT RELATED MATERIAL
PAINT or PAINT RELATED MATERIAL
PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID:	Class: 3	Label: 3
IMDG:	Class: 3	Label: 3
IATA:	Class: 3	Label: 3

Ш



ADR / RID, IMDG, IATA:

14.5. Environmental hazards

ADR / RID:	NO
IMDG:	NO
IATA:	NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
	Special provision: 163, 3	367, 650	
IMDG:	EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Passengers:	Maximum quantity: 60 L	Packaging instructions: 355
	Special provision:	A3, A72, A192	



ΕN

SECTION 14. Transport information ... / >>

14.7. Maritime transport in bulk according to IMO in	nstruments
--	------------

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and env	vironmental regulations/legislation specific for the substance or mixture
Seveso Category - Directi	<u>ve 2012/18/EU:</u> P5c
Product	e product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006
Point Contained substance	3 - 40
Contained substance Point	75
1 Onit	15
Regulation (EU) 2019/114 not applicable	8 - on the marketing and use of explosives precursors
Substances in Candidate On the basis of available of	<u>List (Art. 59 REACH)</u> data, the product does not contain any SVHC in percentage ≥ than 0,1%.
<u>Substances subject to aut</u> None	thorisation (Annex XIV REACH)
<u>Substances subject to exp</u> None	portation reporting pursuant to Regulation (EU) 649/2012:
Substances subject to the	Rotterdam Convention
None	
Substances subject to the None	Stockholm Convention:
<u>Healthcare controls</u> Workers exposed to this c	chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks
	alth and safety are modest and that the 98/24/EC directive is respected.
VOC (Directive 2004/42/E	
One - pack performance c	oatings.
IE 2. Chamical asfaty assa	a coment
15.2. Chemical safety asses	ssment
A chemical safety assess	nent has not been performed for the preparation/for the substances indicated in section 3.
SECTION 16. Other	information
	Information
Text of hazard (H) indication	ons mentioned in section 2-3 of the sheet:
Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1 Aquatic Chronic 1	Hazardous to the aquatic environment, acute toxicity, category 1 Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 1 Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 1 Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.

Causes serious eye irritation.

Causes skin irritation.

H319 H315



SECTION 16. Other information ... / >>

H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 6. Regulation (EU) 944/2013 (V Atp. CLP) of the European Panlament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)

- The Merck Index. - 10th Edition

- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy





SECTION 16. Other information ... / >>

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review: The following sections were modified: 02 / 03 / 08 / 10 / 11 / 12 / 16.