



# VITEX S.A.

## PAINT REMOVER

Revision nr.6  
Dated 22/03/2023  
Printed on 05/09/2023  
Page n. 1 / 12  
Replaced revision:5 (Dated 27/06/2022)

EN

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name **PAINT REMOVER**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Paint Stripper**

#### 1.3. Details of the supplier of the safety data sheet

Name **VITEX S.A.**  
Full address **IMEROS TOPOS**  
District and Country **19300 ASPROPYRGOS (ATTIKI)**  
**GREECE**  
Tel. **(0030) 2105589400**  
Fax **(0030) 2105597859**

e-mail address of the competent person responsible for the Safety Data Sheet **vitexlab@vitex.gr**

Supplier: **VITEX S.A**

#### 1.4. Emergency telephone number

For urgent inquiries refer to **(0030) 2105589400**  
**(0030) 2107793777**

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Eye irritation, category 2	H319	Causes serious eye irritation.
Specific target organ toxicity - single exposure, category 2	H371	May cause damage to organs.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

<b>H225</b>	Highly flammable liquid and vapour.
<b>H319</b>	Causes serious eye irritation.
<b>H371</b>	May cause damage to organs.

Precautionary statements:



# VITEX S.A.

## PAINT REMOVER

Revision nr.6  
Dated 22/03/2023  
Printed on 05/09/2023  
Page n. 2 / 12  
Replaced revision:5 (Dated 27/06/2022)

EN

### SECTION 2. Hazards identification ... / >>

<b>P405</b>	Store locked up.
<b>P501</b>	Dispose of contents / container in accordance with local and national regulations.
<b>P102</b>	Keep out of reach of children.
<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P233</b>	Keep container tightly closed.
<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>P101</b>	If medical advice is needed, have product container or label at hand.
<b>P260</b>	Do not breathe dust / fume / gas / mist / vapours / spray.

**Contains:** METHANOL  
1,3-DIOXOLANE

Product not intended for uses provided for by Directive 2004/42/EC.

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

### SECTION 3. Composition/information on ingredients

#### 3.2. Mixtures

Contains:

Identification		x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>1,3-DIOXOLANE</b>			
INDEX	605-017-00-2	50 ≤ x < 70	<b>Flam. Liq. 2 H225, Eye Irrit. 2 H319</b>
EC	211-463-5		
CAS	646-06-0		
REACH Reg.	01-2119490744-29-XXXX		
<b>ACETONE</b>			
INDEX	606-001-00-8	3 ≤ x < 5	<b>Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066</b>
EC	200-662-2		
CAS	67-64-1		
<b>METHANOL</b>			
INDEX	603-001-00-X	2 ≤ x < 4	<b>Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370</b> <b>STOT SE 2 H371: ≥ 3%</b> <b>STA Oral: 100 mg/kg, STA Dermal: 300 mg/kg, STA Inhalation vapours: 3 mg/l, STA Inhalation mists/powders: 0,501 mg/l</b>
EC	200-659-6		
CAS	67-56-1		
<b>HYDROCARBONS, C10-C13, n-ALKANES, ISOALKANES, CYCLICS, &lt;2% AROMATICS</b>			
INDEX		0 ≤ x < 0,2	<b>Asp. Tox. 1 H304, EUH066</b>
EC	918-481-9		
CAS	64742-48-9		
REACH Reg.	01-2119457273-XXXX		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### SECTION 4. First aid measures

#### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.



# VITEX S.A.

## PAINT REMOVER

Revision nr.6  
Dated 22/03/2023  
Printed on 05/09/2023  
Page n. 3 / 12  
Replaced revision:5 (Dated 27/06/2022)

EN

### SECTION 4. First aid measures ... / >>

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

### SECTION 5. Firefighting measures

#### 5.1. Extinguishing media

##### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

##### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

#### 5.2. Special hazards arising from the substance or mixture

##### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

#### 5.3. Advice for firefighters

##### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

##### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### SECTION 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

### SECTION 7. Handling and storage

#### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.



# VITEX S.A.

## PAINT REMOVER

Revision nr.6  
Dated 22/03/2023  
Printed on 05/09/2023  
Page n. 4 / 12  
Replaced revision:5 (Dated 27/06/2022)

EN

### SECTION 7. Handling and storage ... / >>

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

### SECTION 8. Exposure controls/personal protection

#### 8.1. Control parameters

Regulatory References:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénym a mutagénym faktorom pri práci v znení neskorších predpisov
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

#### ACETONE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	600		1400		
TLV	CZE	800	331,2	1500	621	
AGW	DEU	1200	500	2400 (C)	1000 (C)	
MAK	DEU	1200	500	2400	1000	
VLEP	FRA	1210	500	2420	1000	
TLV	GRC	1780		3560		
AK	HUN	1210				
GVI/KGVI	HRV	1210	500			
TLV	ROU	1210	500			
NPEL	SVK	1210	500			
WEL	GBR	1210	500	3620	1500	
OEL	EU	1210	500			
TLV-ACGIH			250		500	



# VITEX S.A.

## PAINT REMOVER

Revision nr.6  
Dated 22/03/2023  
Printed on 05/09/2023  
Page n. 5 / 12  
Replaced revision:5 (Dated 27/06/2022)

EN

### SECTION 8. Exposure controls/personal protection ... / >>

#### METHANOL

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	260	200			SKIN
TLV	CZE	250	187,75	1000	751	SKIN
AGW	DEU	270	200	1080	800	SKIN
MAK	DEU	130	100	260	200	SKIN
VLEP	FRA	260	200	1300	1000	SKIN 11
TLV	GRC	260	200	325	250	
AK	HUN	260				SKIN
GVI/KGVI	HRV	260	200			SKIN
TLV	ROU	260	200			SKIN
NPEL	SVK	260	200			SKIN
WEL	GBR	266	200	333	250	SKIN
OEL	EU	260	200			
TLV-ACGIH		262	200	328	250	SKIN

#### HYDROCARBONS, C10-C13, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU	300	50	600	100	
OEL	EU	1200				

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose value of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

### SECTION 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

**Properties**  
Appearance  
Colour

**Value**  
viscous liquid  
colourless

**Information**



# VITEX S.A.

## PAINT REMOVER

Revision nr.6  
Dated 22/03/2023  
Printed on 05/09/2023  
Page n. 6 / 12  
Replaced revision:5 (Dated 27/06/2022)

EN

### SECTION 9. Physical and chemical properties ... / >>

Odour	not available		
Melting point / freezing point	not available		
Initial boiling point	> 35 °C		
Flammability	not available		
Lower explosive limit	not available		
Upper explosive limit	not available		
Flash point	< 23 °C		
Auto-ignition temperature	not available		
Decomposition temperature	not available		
pH	not available		
Kinematic viscosity	not available		
Solubility	insoluble in water		
Partition coefficient: n-octanol/water	not available		
Vapour pressure	not available		
Density and/or relative density	0,97-1,01	kg/l	Method:ISO 2811
Relative vapour density	not available		
Particle characteristics	not applicable		

#### 9.2. Other information

##### 9.2.1. Information with regard to physical hazard classes

Information not available

##### 9.2.2. Other safety characteristics

Information not available

### SECTION 10. Stability and reactivity

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

##### ACETONE

Decomposes under the effect of heat.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

##### ACETONE

Risk of explosion on contact with: bromine trifluoride, fluorine dioxide, hydrogen peroxide, nitrosyl chloride, 2-methyl-1,3 butadiene, nitromethane, nitrosyl perchlorate. May react dangerously with: potassium tert-butoxide, alkaline hydroxides, bromine, bromoform, isoprene, sodium, sulphur dioxide, chromium trioxide, chromyl chloride, nitric acid, chloroform, peroxy monosulphuric acid, phosphoryl oxychloride, chromosulphuric acid, fluorine, strong oxidising agents, strong reducing agents. Develops flammable gas on contact with: nitrosyl perchlorate.

#### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

##### ACETONE

Avoid exposure to: sources of heat, naked flames.

#### 10.5. Incompatible materials

##### ACETONE

Incompatible with: acids, oxidising substances.

#### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

##### ACETONE

May develop: ketenes, irritant substances.



# VITEX S.A.

## PAINT REMOVER

Revision nr.6  
Dated 22/03/2023  
Printed on 05/09/2023  
Page n. 7 / 12  
Replaced revision:5 (Dated 27/06/2022)

EN

### SECTION 11. Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

##### Information on likely routes of exposure

METHANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

##### Delayed and immediate effects as well as chronic effects from short and long-term exposure

METHANOL

The minimum lethal dose for humans by ingestion is considered to be in the range from 300 to 1000 mg/kg. Ingestion of 4-10 ml of the substance may cause permanent blindness in adult humans (IPCS).

##### Interactive effects

Information not available

##### ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

METHANOL

STA (Oral): 100 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

STA (Dermal): 300 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

STA (Inhalation mists/powders): 0,501 mg/l estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

STA (Inhalation vapours): 3 mg/l estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

HYDROCARBONS, C10-C13, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

LD50 (Dermal): > 5000 mg/kg

LD50 (Oral): > 5000 mg/kg

LC50 (Inhalation vapours): > 20 mg/l/4h Rat

##### SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

##### SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

##### RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

##### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

##### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

##### REPRODUCTIVE TOXICITY



# VITEX S.A.

## PAINT REMOVER

Revision nr.6  
Dated 22/03/2023  
Printed on 05/09/2023  
Page n. 8 / 12  
Replaced revision:5 (Dated 27/06/2022)

EN

### SECTION 11. Toxicological information ... / >>

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

May cause damage to organs

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

#### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

### SECTION 12. Ecological information

#### 12.1. Toxicity

HYDROCARBONS, C10-C13, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

LC50 - for Fish	> 100 mg/l/96h
EC50 - for Crustacea	> 100 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
Chronic NOEC for Fish	> 0,1 mg/l based on modeled data
Chronic NOEC for Crustacea	> 0,1 mg/l based on modeled data

#### 12.2. Persistence and degradability

HYDROCARBONS, C10-C13, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Rapidly degradable

METHANOL

Solubility in water 1000 - 10000 mg/l  
Rapidly degradable

ACETONE

Rapidly degradable

#### 12.3. Bioaccumulative potential

METHANOL

Partition coefficient: n-octanol/water -0,77  
BCF 0,2

ACETONE

Partition coefficient: n-octanol/water -0,23  
BCF 3

#### 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

#### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.





# VITEX S.A.

## PAINT REMOVER

Revision nr.6  
Dated 22/03/2023  
Printed on 05/09/2023  
Page n. 9 / 12  
Replaced revision:5 (Dated 27/06/2022)

EN

### SECTION 12. Ecological information ... / >>

#### 12.7. Other adverse effects

Information not available

### SECTION 13. Disposal considerations

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### SECTION 14. Transport information

#### 14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1263

#### 14.2. UN proper shipping name

ADR / RID: PAINT RELATED MATERIAL  
IMDG: PAINT RELATED MATERIAL  
IATA: PAINT RELATED MATERIAL

#### 14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



#### 14.4. Packing group

ADR / RID, IMDG, IATA: II

#### 14.5. Environmental hazards

ADR / RID: NO  
IMDG: NO  
IATA: NO

#### 14.6. Special precautions for user

ADR / RID: HIN - Kemler: 33 Limited Quantities: 5 L  
Special provision: 163, 367, 640C, 650  
IMDG: EMS: F-E, S-E Limited Quantities: 5 L  
IATA: Cargo: Maximum quantity: 60 L  
Passengers: Maximum quantity: 5 L  
Special provision: A3, A72, A192

Tunnel restriction code: (D/E)

Packaging instructions: 364  
Packaging instructions: 353

#### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant



# VITEX S.A.

## PAINT REMOVER

Revision nr.6  
Dated 22/03/2023  
Printed on 05/09/2023  
Page n. 10 / 12  
Replaced revision:5 (Dated 27/06/2022)

EN

### SECTION 15. Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Point 69 METHANOL

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Regulated explosives precursor

The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.

All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors, amending Regulation (EC) No 1907/2006 and repealing Regulation (EU) No 98/2013

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

### SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Acute Tox. 3	Acute toxicity, category 3
STOT SE 1	Specific target organ toxicity - single exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
Eye Irrit. 2	Eye irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
STOT SE 2	Specific target organ toxicity - single exposure, category 2
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H371	May cause damage to organs.



# VITEX S.A.

## PAINT REMOVER

Revision nr.6  
Dated 22/03/2023  
Printed on 05/09/2023  
Page n. 11 / 12  
Replaced revision:5 (Dated 27/06/2022)

EN

### SECTION 16. Other information ... / >>

**EUH066**

Repeated exposure may cause skin dryness or cracking.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
  4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2019/521 (XII Atp. CLP)
  16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
  17. Regulation (EU) 2019/1148
  18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
  19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
  20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
  21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
  22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:



# VITEX S.A.

## PAINT REMOVER

Revision nr.6  
Dated 22/03/2023  
Printed on 05/09/2023  
Page n. 12 / 12  
Replaced revision:5 (Dated 27/06/2022)

EN

### SECTION 16. Other information ... / >>

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

02 / 03 / 05 / 07 / 08 / 09 / 11 / 12 / 16.