



# VITEX S.A.

## SPRAY'T COLOR

Revision nr.2  
Dated 11/04/2022  
Printed on 12/04/2022  
Page n. 1 / 14  
Replaced revision:1 (Dated 24/02/2020)

EN

## Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name **SPRAY'T COLOR**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **General Use Acrylic paint in various shades for different surfaces and specialized applications**

#### 1.3. Details of the supplier of the safety data sheet

Name **VITEX S.A.**  
Full address **IMEROS TOPOS**  
District and Country **19300 ASPROPYRGOS (ATTIKI)**  
**GREECE**  
Tel. **(0030) 2105589400**  
Fax **(0030) 2105597859**

e-mail address of the competent person responsible for the Safety Data Sheet **vitexlab@vitex.gr**

Supplier: **VITEX S.A**

#### 1.4. Emergency telephone number

For urgent inquiries refer to **(0030) 2105589400**  
**(0030) 2107793777**

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222	Extremely flammable aerosol.
	H229	Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

<b>H222</b>	Extremely flammable aerosol.
<b>H229</b>	Pressurised container: may burst if heated.
<b>H319</b>	Causes serious eye irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.



# VITEX S.A.

## SPRAY'T COLOR

Revision nr.2  
Dated 11/04/2022  
Printed on 12/04/2022  
Page n. 2 / 14  
Replaced revision:1 (Dated 24/02/2020)

EN

### SECTION 2. Hazards identification ... / >>

Precautionary statements:

<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P211</b>	Do not spray on an open flame or other ignition source.
<b>P251</b>	Do not pierce or burn, even after use.
<b>P271</b>	Use only outdoors or in a well-ventilated area.
<b>P312</b>	Call a POISON CENTRE / doctor / . . . if you feel unwell.
<b>P410+P412</b>	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
<b>P501</b>	Dispose of contents / container in accordance with local and national regulations.
<b>P101</b>	If medical advice is needed, have product container or label at hand.
<b>P102</b>	Keep out of reach of children.
<b>P103</b>	Read label before use.
<b>P405</b>	Store locked up.

**Contains:** N-BUTYL ACETATE  
METHYL ACETATE

Product not intended for uses provided for by Directive 2004/42/EC.

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

### SECTION 3. Composition/information on ingredients

#### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)	
<b>METHYL ACETATE</b>			
CAS	79-20-9	$30 \leq x < 35$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC	201-185-2		
INDEX	607-021-00-X		
<b>N-BUTYL ACETATE</b>			
CAS	123-86-4	$10 \leq x < 15$	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
EC	204-658-1		EUH066: $\geq$ 0%
INDEX	607-025-00-1		
<b>XYLENE (MIXTURE OF ISOMERS)</b>			
CAS	1330-20-7	$4 \leq x < 7$	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C STA Dermal: 1100 mg/kg, STA Inhalation mists/powders: 1,5 mg/l
EC	215-535-7		
INDEX	601-022-00-9		
REACH Reg.	01-2119488216-XXXX		
<b>ACETONE</b>			
CAS	67-64-1	$3 \leq x < 4$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC	200-662-2		
INDEX	606-001-00-8		
<b>2-BUTOXYETHANOL</b>			
CAS	111-76-2	$3 \leq x < 4$	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC	203-905-0		LD50 Oral: 615 mg/l/4h, STA Dermal: 1100 mg/kg, STA Inhalation mists/powders: 1,5 mg/l
INDEX	603-014-00-0		
REACH Reg.	01-2119475108-36		



# VITEX S.A.

## SPRAY'T COLOR

Revision nr.2  
Dated 11/04/2022  
Printed on 12/04/2022  
Page n. 3 / 14  
Replaced revision:1 (Dated 24/02/2020)

EN

### SECTION 3. Composition/information on ingredients ... / >>

#### METHANOL

CAS 67-56-1  $1 \leq x < 3$

EC 200-659-6  
INDEX 603-001-00-X

REACH Reg. 01-2119433307-44

Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370  
STOT SE 2 H371:  $\geq 3\%$   
STA Oral: 100 mg/kg, STA Dermal: 300 mg/kg, STA Inhalation mists/powders: 0,501 mg/l

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 34,50 %

### SECTION 4. First aid measures

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

### SECTION 5. Firefighting measures

#### 5.1. Extinguishing media

##### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

##### UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

##### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

#### 5.3. Advice for firefighters

##### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

##### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### SECTION 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

#### 6.2. Environmental precautions

Do not disperse in the environment.



# VITEX S.A.

## SPRAY'T COLOR

Revision nr.2  
Dated 11/04/2022  
Printed on 12/04/2022  
Page n. 4 / 14  
Replaced revision:1 (Dated 24/02/2020)

EN

### SECTION 6. Accidental release measures ... / >>

#### 6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

### SECTION 7. Handling and storage

#### 7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

#### 7.3. Specific end use(s)

Information not available

### SECTION 8. Exposure controls/personal protection

#### 8.1. Control parameters

Regulatory References:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemijskim tvarima na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénym a mutagénym faktorom pri práci v znení neskorších predpisov
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021



# VITEX S.A.

## SPRAY'T COLOR

Revision nr.2  
Dated 11/04/2022  
Printed on 12/04/2022  
Page n. 5 / 14  
Replaced revision:1 (Dated 24/02/2020)

EN

### SECTION 8. Exposure controls/personal protection ... / >>

#### METHYL ACETATE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	600	195	800	260	
AGW	DEU	620	200	1240 (C)	400 (C)	
MAK	DEU	310	100	1240	400	
VLEP	FRA	610	200	760	250	SKIN
TLV	GRC	610	200	760	250	
AK	HUN	310		1240		SKIN
GVI/KGVI	HRV	616	200	770	250	
TLV	ROU	200	63	600	188	
NPEL	SVK	310	100	770	250	
WEL	GBR	616	200	770	250	
TLV-ACGIH		606	200	757	250	

#### N-BUTYL ACETATE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	950		1200		
MAK	DEU		100		200	
VLEP	FRA	710	150	940	200	
TLV	GRC	710	150	950	200	
AK	HUN	950		950		
NPEL	SVK	480	100			
WEL	GBR		150		200	
TLV-ACGIH			150		200	

#### XYLENE (MIXTURE OF ISOMERS)

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	221		442		SKIN
TLV	CZE	200		400		SKIN
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLEP	FRA	221	50	442	100	SKIN
TLV	GRC	435	100	650	150	SKIN
AK	HUN	221		442		SKIN
GVI/KGVI	HRV	221	50	442	100	SKIN
NPEL	SVK	221	50	442		SKIN
WEL	GBR	220	50	441	100	
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d



# VITEX S.A.

## SPRAY'T COLOR

Revision nr.2  
Dated 11/04/2022  
Printed on 12/04/2022  
Page n. 6 / 14  
Replaced revision:1 (Dated 24/02/2020)

EN

### SECTION 8. Exposure controls/personal protection ... />>

#### ACETONE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	600		1400		
TLV	CZE	800	331,2	1500	621	
AGW	DEU	1200	500	2400 (C)	1000 (C)	
MAK	DEU	1200	500	2400	1000	
VLEP	FRA	1210	500	2420	1000	
TLV	GRC	1780		3560		
AK	HUN	1210				
GVI/KGVI	HRV	1210	500			
TLV	ROU	1210	500			
NPEL	SVK	1210	500			
WEL	GBR	1210	500	3620	1500	
OEL	EU	1210	500			
TLV-ACGIH			250		500	

#### 2-BUTOXYETHANOL

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	98		246		SKIN
TLV	CZE	100		200		SKIN
AGW	DEU	49	10	196	40	SKIN
MAK	DEU	49	10	98	20	SKIN
VLEP	FRA	49	10	246	50	SKIN
TLV	GRC	120	25			
AK	HUN	98		246		
GVI/KGVI	HRV	98	20	246	50	SKIN
NPEL	SVK	98	20	246		SKIN
WEL	GBR	123	25	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

##### Predicted no-effect concentration - PNEC

Normal value in fresh water	8,8	mg/l
Normal value of STP microorganisms	463	mg/l
Normal value for the terrestrial compartment	2,8	mg/kg

##### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	VND	13,4 mg/kg						
Inhalation	VND	426 mg/m3			VND	663 mg/m3		
Skin	VND	44,5 mg/kg			VND	89 mg/kg		

#### METHANOL

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	50				SKIN
TLV	CZE	250		1000		SKIN
AGW	DEU	270	200	1080	800	SKIN
MAK	DEU	270	200	1080	800	SKIN
VLEP	FRA	260	200	1300	1000	SKIN
TLV	GRC	260	200	325	250	
AK	HUN	260		1040		
GVI/KGVI	HRV	260	200			SKIN
NPEL	SVK	260	200			SKIN
WEL	GBR	266	200	333	250	SKIN
OEL	EU	260	200			SKIN
TLV-ACGIH		262	200	328	250	

##### Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.



# VITEX S.A.

## SPRAY'T COLOR

Revision nr.2  
Dated 11/04/2022  
Printed on 12/04/2022  
Page n. 7 / 14  
Replaced revision:1 (Dated 24/02/2020)

EN

### SECTION 8. Exposure controls/personal protection ... />>

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

##### HAND PROTECTION

None required.

##### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

##### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

##### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

##### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

### SECTION 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	aerosol	
Colour	as showed in color folder	
Odour	characteristic of solvent	
Melting point / freezing point	Not available	
Initial boiling point	Not applicable	
Flammability	flammable gas	
Lower explosive limit	Not available	
Upper explosive limit	Not available	
Flash point	Not applicable	
Auto-ignition temperature	Not available	
pH	Not available	
Kinematic viscosity	Not available	
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	Not available	
Vapour pressure	4,0 bar	
Density and/or relative density	0,75 - 0,85	
Relative vapour density	Not available	
Particle characteristics	Not applicable	

#### 9.2. Other information

##### 9.2.1. Information with regard to physical hazard classes

Information not available

##### 9.2.2. Other safety characteristics

Information not available

### SECTION 10. Stability and reactivity

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

##### ACETONE

Decomposes under the effect of heat.

##### 2-BUTOXYETHANOL



# VITEX S.A.

## SPRAY'T COLOR

Revision nr.2  
Dated 11/04/2022  
Printed on 12/04/2022  
Page n. 8 / 14  
Replaced revision:1 (Dated 24/02/2020)

EN

### SECTION 10. Stability and reactivity ... / >>

2-BUTOXYETHANOL: decomposes in the presence of heat.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

##### ACETONE

Risk of explosion on contact with: bromine trifluoride, fluorine dioxide, hydrogen peroxide, nitrosyl chloride, 2-methyl-1,3 butadiene, nitromethane, nitrosyl perchlorate. May react dangerously with: potassium tert-butoxide, alkaline hydroxides, bromine, bromoform, isoprene, sodium, sulphur dioxide, chromium trioxide, chromyl chloride, nitric acid, chloroform, peroxymonosulphuric acid, phosphoryl oxychloride, chromosulphuric acid, fluorine, strong oxidising agents, strong reducing agents. Develops flammable gas on contact with: nitrosyl perchlorate.

##### 2-BUTOXYETHANOL

2-BUTOXYETHANOL: can react dangerously with: aluminium, oxidising agents. Forms peroxide with air.

#### 10.4. Conditions to avoid

Avoid overheating.

##### ACETONE

Avoid exposure to: sources of heat, naked flames.

##### 2-BUTOXYETHANOL

2-BUTOXYETHANOL: avoid exposure to sources of heat and naked flames.

#### 10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

##### ACETONE

Incompatible with: acids, oxidising substances.

#### 10.6. Hazardous decomposition products

##### ACETONE

May develop: ketenes, irritant substances.

##### 2-BUTOXYETHANOL

2-BUTOXYETHANOL: hydrogen.

### SECTION 11. Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### METHANOL

METHANOL: The minimal lethal dose following ingestion is considered to be in the range of 300-1000 mg/kg. Ingestion of as little as 4-10 ml methanol in adults may cause permanent blindness (IPCS).

##### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

##### Information on likely routes of exposure

Information not available

##### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

##### Interactive effects

Information not available

##### ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture: > 5 mg/l  
ATE (Oral) of the mixture: >2000 mg/kg  
ATE (Dermal) of the mixture: >2000 mg/kg





# VITEX S.A.

## SPRAY'T COLOR

Revision nr.2  
Dated 11/04/2022  
Printed on 12/04/2022  
Page n. 9 / 14  
Replaced revision:1 (Dated 24/02/2020)

EN

### SECTION 11. Toxicological information ... / >>

N-BUTYL ACETATE	
LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 6400 mg/kg Rat
LC50 (Inhalation vapours):	21,1 mg/l/4h Rat
XYLENE (MIXTURE OF ISOMERS)	
STA (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	> 2000 mg/kg Rat
LC50 (Inhalation vapours):	> 10 mg/l/4h Rat
STA (Inhalation mists/powders):	1,5 mg/l (figure used for calculation of the acute toxicity estimate of the mixture)
2-BUTOXYETHANOL	
LD50 (Dermal):	405 mg/kg Rabbit
STA (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	615 mg/kg Rat
LC50 (Inhalation vapours):	2,2 mg/l/4h Rat
STA (Inhalation mists/powders):	1,5 mg/l (figure used for calculation of the acute toxicity estimate of the mixture)
METHANOL	
LD50 (Dermal):	> 2000 mg/kg Rat
STA (Dermal):	300 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	> 2000 mg/kg Rat
STA (Oral):	100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LC50 (Inhalation vapours):	> 20 mg/l/4h Rat
STA (Inhalation mists/powders):	0,501 mg/l (figure used for calculation of the acute toxicity estimate of the mixture)

#### SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

#### SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

#### RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

##### Respiratory sensitization

Information not available

##### Skin sensitization

Information not available

#### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

##### Adverse effects on sexual function and fertility

Information not available

##### Adverse effects on development of the offspring



# VITEX S.A.

## SPRAY'T COLOR

Revision nr.2  
Dated 11/04/2022  
Printed on 12/04/2022  
Page n. 10 / 14  
Replaced revision:1 (Dated 24/02/2020)

EN

### SECTION 11. Toxicological information ... / >>

Information not available

#### Effects on or via lactation

Information not available

#### STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

#### Target organs

Information not available

#### Route of exposure

Information not available

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### Target organs

Information not available

#### Route of exposure

Information not available

#### ASPIRATION HAZARD

Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth

#### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

### SECTION 12. Ecological information

#### 12.1. Toxicity

##### XYLENE (MIXTURE OF ISOMERS)

LC50 - for Fish	> 1 mg/l/96h
EC50 - for Crustacea	> 1 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 1 mg/l/72h
Chronic NOEC for Fish	> 1 mg/l based on test data
Chronic NOEC for Crustacea	> 0,1 mg/l

#### 12.2. Persistence and degradability

##### 2-BUTOXYETHANOL

Rapidly degradable

##### XYLENE (MIXTURE OF ISOMERS)

Rapidly degradable

##### ACETONE

Rapidly degradable

##### METHYL ACETATE

Solubility in water 243500 mg/l

Rapidly degradable

#### 12.3. Bioaccumulative potential



# VITEX S.A.

## SPRAY'T COLOR

Revision nr.2  
Dated 11/04/2022  
Printed on 12/04/2022  
Page n. 11 / 14  
Replaced revision:1 (Dated 24/02/2020)

EN

### SECTION 12. Ecological information ... / >>

2-BUTOXYETHANOL  
Partition coefficient: n-octanol/water 0,81

XYLENE (MIXTURE OF ISOMERS)  
Partition coefficient: n-octanol/water 3,12

ACETONE  
Partition coefficient: n-octanol/water -0,23  
BCF 3

METHYL ACETATE  
Partition coefficient: n-octanol/water 0,18

#### 12.4. Mobility in soil

METHYL ACETATE  
Partition coefficient: soil/water 0,18

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

#### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

### SECTION 13. Disposal considerations

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### SECTION 14. Transport information

#### 14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1950

#### 14.2. UN proper shipping name

ADR / RID: AEROSOLS

IMDG: AEROSOLS

IATA: AEROSOLS



# VITEX S.A.

## SPRAY'T COLOR

Revision nr.2  
Dated 11/04/2022  
Printed on 12/04/2022  
Page n. 12 / 14  
Replaced revision:1 (Dated 24/02/2020)

EN

### SECTION 14. Transport information ... / >>

#### 14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1



IMDG: Class: 2 Label: 2.1



IATA: Class: 2 Label: 2.1



#### 14.4. Packing group

ADR / RID, IMDG, IATA: -

#### 14.5. Environmental hazards

ADR / RID: NO  
IMDG: NO  
IATA: NO

#### 14.6. Special precautions for user

ADR / RID:	HIN - Kemler: -- Special provision: -	Limited Quantities: 1 L	Tunnel restriction code: (D)
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo: Pass.: Special provision:	Maximum quantity: 150 Kg Maximum quantity: 75 Kg A145, A167, A802	Packaging instructions: 203 Packaging instructions: 203

#### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

### SECTION 15. Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Contained substance

Point 75

Point 69

METHANOL

REACH Reg.: 01-2119433307-44

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Regulated explosives precursor

The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.

All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None



# VITEX S.A.

## SPRAY'T COLOR

Revision nr.2  
Dated 11/04/2022  
Printed on 12/04/2022  
Page n. 13 / 14  
Replaced revision:1 (Dated 24/02/2020)

EN

### SECTION 15. Regulatory information ... / >>

Substances subject to the Stockholm Convention:

None

#### Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

### SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Aerosol 1</b>	Aerosol, category 1
<b>Aerosol 3</b>	Aerosol, category 3
<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Acute Tox. 3</b>	Acute toxicity, category 3
<b>STOT SE 1</b>	Specific target organ toxicity - single exposure, category 1
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>H222</b>	Extremely flammable aerosol.
<b>H229</b>	Pressurised container: may burst if heated.
<b>H225</b>	Highly flammable liquid and vapour.
<b>H301</b>	Toxic if swallowed.
<b>H311</b>	Toxic in contact with skin.
<b>H331</b>	Toxic if inhaled.
<b>H370</b>	Causes damage to organs.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit



# VITEX S.A.

## SPRAY'T COLOR

Revision nr.2  
Dated 11/04/2022  
Printed on 12/04/2022  
Page n. 14 / 14  
Replaced revision:1 (Dated 24/02/2020)

EN

### SECTION 16. Other information ... / >>

- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 10 / 11 / 12 / 15 / 16.