

ACRYLIC PUTTY

Acrylic Repair Putty

White water-based acrylic putty for interior and exterior use. It exhibits excellent resistance to adverse weather conditions, damp, alkalinity and is suitable for tilling and coating of plaster, concrete, wood and for decorative applications. It has excellent working properties and dries fast without cracking. It is easy to sand and gives a smooth surface.



Advantages:

- Excellent filling, easy to sand and gives a smooth surface
- For interior and exterior use

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

370.000-800.000 cps
(BROOKFIELD
sp.7/50rpm, 25° C)

COVERAGE



2-3 m²/Kg

DRYING TIME



Touch dry

30 min

For top coat application

3-4 h

PACKAGING

White

400 gr


800 gr

5 kg



COLOURS

White



APPLICATION

APPLICATION FIELD

For filling and coating of plaster, concrete and wood in interior or exterior areas.

PREPARATION



Surfaces must be must be clean, dry and smooth, free from dust, grease, loose material.

CONSTRUCTION APPLICATIONS - PUTTIES

APPLICATION

STEPS

- 1 The putty is ready to use. Apply the product using a spatula without dilution.

- 2 After 2-3 hours, the product is rubbed with sandpaper, clean the surface and apply with any emulsion or acrylic water-based or solvent-based paint of Vitex.

TIPS

- Application at 5-35°C and <80% RH. For exterior use do not apply if there is a risk of rain/frost in the next 48 hours.
- After the application, seal the container and store it for future use.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
- Do not dispose of liquid waste into ground water table. Unused material requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCS (Volatile Organic Compounds)



"Primers", VOC content limit **30 g/L**.
Maximum VOC content **29 g/L** VOCs
(ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request.
Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Containers must be kept closed in a
shady place away from direct sunlight.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT



VITEX S.A., P.O. Box. 139 Imeros Topos, Aspropyrgos GR 193 00 | Tel. +30 210 5589500, Fax +30 210 4835007 | www.vitex.gr

Version: 12.2020 (This datasheet supersedes all previous versions)