

DIAXYL PLUS SB

PU Wood Stain Solvent-based

Protective and decorative polyurethane solvent-based penetration varnish for interior and exterior wooden surfaces. Due to its special formulation prevents effectively the growth of mould and fungi in the film. It penetrates through the wood pores forming a thin film, allowing it at the same time to breathe. Due to its elasticity follows wood's contraction and protects it from moisture and UV radiation.

Advantages:

- Protective and decorative varnish for exterior and interior wooden surfaces
- With polyurethane and UV filters for excellent durability and resistance to adverse weather conditions and UV radiation
- Allows wood to "breathe"



Paints with polyurethane resins for enhanced durability



Paints with UV filters for protection from sunlight

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

40 ± 10 KU (ASTM D 562, 25° C)

Density

0,85 ± 0,02 Kg / L (ISO 2811)

FINISH

Natural	Satin	Gloss
✓		
Natural Finish		

DILUTION




Undiluted

Ready for use

COLOURS

Colorless and 11 ready-made shades




COVERAGE



One coat

12-16 m²/L



Two coats

6-8 m²/L

DRYING TIME



Touch dry

2-3 h

Recoat

24 h

COLOR CARDS - FANDECKS



PACKAGING

Colorless and 11 ready-made shades	750 mL	2.5 L
------------------------------------	--------	-------



WOOD PROTECTION

APPLICATION

APPLICATION FIELD

For interior and exterior wooden surfaces.

PREPARATION



Surfaces should be smooth, clean, dry, free from grease, rosins or old varnishes.



On new wooden surfaces apply preservative Diaxyl Extra solvent-based for protection against fungi and insects.



STEPS

1 Stir well before use.

2 Apply the first coat by brush, roller or spray gun.

3 Recoat ,if desired, after 24 hours.

TIPS

- Application at 5-35°C and <80% RH and wood moisture should not exceed 18%.
- The final shade of the wooden surface depends on the natural colour and absorbency of the wood, as well as the number of coats of Diaxyl Plus.

- Clean rollers, brushes with Brush Solvent T-300 and then with soapy water or detergent. Use Spray Gun Solvent T-350 to clean spray guns.
- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After

- paint application, seal the container and store it for future use.
- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Interior and exterior minimal build woodstains", VOC content limit **700 g/L**. Maximum VOC content **699 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

