

ELASTOMERIC PUTTY

Elastomeric Putty

Elastomeric water-based acrylic putty that can be used for repair and waterproofing of interior and exterior surfaces. It contains microspheres attributing characteristics that make it ideal for repairing cracks and joints, since it hardly shrinks and does not crack. It has a high resistance to humidity, changes in temperature, alkalinity, external weather resistance and is used on surfaces such as concrete, brick, plaster, cement, wood, plasterboard. It has strong adhesion, it is simple to use and apply and easy to sand.



Advantages:

- Hardly shrinks and does not crack
- For interior and exterior use

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

250.000-470.000 cps
(BROOKFIELD sp.7/50rpm, 25°C)

Density

1,23- ± 0,02 Kg / L (ISO 2811)

COVERAGE



1,5-2,5
m²/Kg

DRYING TIME



Touch dry

3-6 h

For top coat application

1-2 days

PACKAGING

Grey

400 gr


800 gr

4 kg



COLOURS

Grey



APPLICATION

APPLICATION FIELD

For repair and waterproofing of interior and exterior surfaces.

PREPARATION



Surfaces must be must be clean, dry and smooth, free from dust, grease, loose material.

CONSTRUCTION APPLICATIONS - PUTTIES

APPLICATION

STEPS

1

The putty is ready to use. Apply the product using a spatula without dilution in cracks up to 1 cm, as well as in larger with the prior use of joint filler cord.

2

Paintable after 1-2 days, depending on the dimensions of the crack-joint and weather conditions (relative humidity and temperature), with any emulsion or acrylic water-based or solvent-based paint of Vitex with the prior use of a suitable primer.

TIPS

- Application at 5-35°C and <80% RH. For exterior use do not apply if there is a risk of rain/frost in the next 48 hours.
- After the application, seal the container

- and store it for future use.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.

- Do not dispose of liquid waste into ground water table. Unused material requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCS (Volatile Organic Compounds)



"Primers", VOC content limit **30 g/L**.
Maximum VOC content **29 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Containers must be kept closed in a shady place away from direct sunlight.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT



VITEX S.A., P.O. Box. 139 Imeros Topos, Aspropyrgos GR 193 00 | Tel. +30 210 5589500, Fax +30 210 4835007 | www.vitex.gr

Version: 12.2020 (This datasheet supersedes all previous versions)