

HARDENER

Air Dry Hardener

Special air dry hardener suitable to react chemically with activated groups of resins contained in enamel paints and varnishes (Syntol, Verolac, etc.). It provides a shorter drying time, increase gloss and hardness. When mixed with the paints above, it creates polyurethane system and secures high resistance of these paints against adverse weather conditions, humidity, acids, alkalis and mechanical strains.

Advantages:

- Maximizes enamel hardness and durability
- Reduces drying time



PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

20 ± 5 sec (FORD CUP#4, 25°C)

Density

0,94 ± 0,02 Kg / L (ISO 2811)

PACKAGING

Transparent 375 mL 750 mL



COLOURS

Transparent



APPLICATION

APPLICATION FIELD

Special hardener for addition to alkyd paints.

APPLICATION



Air-Dry Hardener may be added prior to application. Mix 200 mL Hardener with 1 L paint and stir very well. The mixture must be applied within 1-2 hours after mixing depending on weather conditions (humidity and temperature).



ADDITIONAL INFORMATION

STORAGE



5°C-38°C

Keep containers closed in a cool and dry area.

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

USE



Only for professional use.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

ISO 9001
14001
CERTIFIED 45001

