

LIGHT ACRYLIC PUTTY

Light Acrylic Putty

White, ready to use acrylic ultra light with high opacity putty for filling and repairing cracks and holes in walls, plasterboards and ceilings for interior application. It is easy to use, does not shrink, is fast drying, sandable and paintable with any paint.

Advantages:

- For filling large and small holes and cracks
- Does not shrink, it dries fast and is easy sandable



PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Density
0,60 ± 0,02
Kg / L
(ISO 2811)

DRYING TIME



Touch dry
5-15 min

For top coat application
2-3 h

COLOURS

White



PACKAGING

White 750 mL



 1508	
VITEX S.A. P.O. BOX 139 IMEROS TOPOS ASPROPYRGOS GR 19300 LIGHT ACRYLIC PUTTY 16 DoP No : VIT-CPR-1410002004	
Type 1A -EN 13963 Jointing materials for gypsum plasterboards	
Reaction to fire	Class E
Dangerous substances	NPD
Flexural strength	NPD

APPLICATION

APPLICATION FIELD

For filling and repairing cracks and holes in walls, concrete, gypsumboards etc. in interior areas.

PREPARATION



Surfaces must be must be clean, dry and smooth, free from dust, grease, loose material.

CONSTRUCTION APPLICATIONS - PUTTIES

APPLICATION

STEPS

1 The putty is ready to use. Apply the product using a spatula without dilution.

2 After 1-2 hours, the product is rubbed with sandpaper, clean the surface and apply with any emulsion or acrylic water-based or solvent-based paint of Vitex.

TIPS

- Application at 5-35°C and <80% RH.
- After the application, seal the container and store it for future use.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
- Do not dispose of liquid waste into ground water table. Unused material requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Primers", VOC content limit **30 g/L**.
Maximum VOC content **10 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request.
Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Containers must be kept closed in a shady place away from direct sunlight.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT



VITEX S.A., P.O. Box. 139 Imeros Topos, Aspropyrgos GR 193 00 | Tel. +30 210 5589500, Fax +30 210 4835007 | www.vitex.gr

Version: 12.2020 (This datasheet supersedes all previous versions)