

MARTELITE

Paint For Metal Surfaces with Hammer-Effect Finish

Alkyd hammer-effect solvent-based paint suitable for the protection and decoration of metal surfaces. It provides strong adhesion, quick drying and great durability to adverse weather conditions. It has good working and leveling properties and can be applied directly onto metal without using an undercoat. It gives an excellent hammer-effect finish.



Advantages:

- Protection and decoration of metal surfaces
- Great durability

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

65 ± 5 KU (ASTM D 562, 25°C)

Density

0,98 ± 0,02 Kg / L (ISO 2811) for white

COVERAGE



One coat

8-10 m²/L



Two coats

4-5 m²/L

PACKAGING

13 ready-made shades 750 mL 2.5 L



FINISH

Hammer-Effect Satin Gloss



Hammer-Effect Finish

DILUTION



Up to 5%

With Spray Gun Solvent T350

DRYING TIME



Touch dry

30-60 min

Recoat

2-3h or >7 days

COLOURS

13 ready-made shades



COLOR CARDS - FANDECKS



METAL SURFACES

APPLICATION

APPLICATION FIELD

For all kinds of metal surfaces.

PREPARATION



Surfaces should be cleaned with Brush Solvent T300, be smooth and dry, free from dust, grease or rust and sanded.



Exterior metal surfaces should be first coated with Wash Primer.



STEPS

1

Dilute up to 5% with Spray Gun Solvent T350 and stir well before use.

2

Apply the first coat by brush, roller or spray gun.

3

Recoat after 2-3 hours or otherwise after 7 days.

TIPS

- Application at 5-35°C and <80% RH. For exterior use, don't apply if there is a risk of rain/frost in the next 48 hours.
- Clean rollers, brushes and spray guns with Gun Solvent T350 and then with soapy water or detergent.
- Allow at least 30 days before

- cleaning and washing newly painted surfaces with Martelite.
- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the

- container and store it for future use.
- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"One-pack performance coatings". VOC content limit **500 g/L**. Maximum VOC content **499 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C

Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

