

# PAINT REMOVER

## Paint Remover

Extremely effective paint and varnish remover based on new technology without dichloromethane. Removes from any surface old one or two component paints by penetrating into their film, without affecting it.

### Advantages:

- Acts without affecting the surface
- Without dichloromethane



## PRODUCT FEATURES

### TECHNICAL CHARACTERISTICS



#### Density

0,99 ± 0,02 Kg / L (ISO 2811)


### DILUTION



#### Without dilution

Έτοιμο προς χρήση

### COVERAGE



#### 2-4 m<sup>2</sup>/L

Depending on the paint and type of surface

### PACKAGING

Cans


375 mL

750 mL



### COLOURS

Colourless



### DRYING TIME



#### Touch dry

15-40 min

## APPLICATION

### APPLICATION FIELD

For removing old paint one or two components.

### APPLICATION

- Open container carefully and apply a thick layer of Paint Remover by brush or spatula.
- Leave it on for 10-20 minutes (in two-component paints or varnishes, allow to act for longer).
- Then with a spatula or scraper remove the soft paint. Repeat the process if necessary.
- After removing the old paints or varnishes, clean the surface with water or solvent and after drying it can be re-painted.

# SPECIAL APPLICATIONS

## APPLICATION

### TIPS

- Application at 5-35°C
- Clean brushes, spatulas and floor stains with water and then with soap or detergent.
- Do not dispose of liquid waste into ground water table.
- Unused material requires special handling for safe disposal.

## ADDITIONAL INFORMATION

### STORAGE



**5°C-38°C**

Keep containers closed in a cool and dry area.

### PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request.  
Poisons Control Centre Tel. : +30 210 7793 777

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

**+30.210.5589.400**

**TECHNICAL SUPPORT**



VITEX S.A., P.O. Box. 139 Imeros Topos, Aspropyrgos GR 193 00 | Tel. +30 210 5589500, Fax +30 210 4835007 | [www.vitex.gr](http://www.vitex.gr)

Version: 12.2020 (This datasheet supersedes all previous versions)