

RELIEF

Textured Emulsion Paint

Textured coating based on a vinyl copolymer. It exhibits great hiding power and exceptional resistance to moisture and adverse weather conditions. It has very good levelling properties and forms a hard, non-cracking finish. It can be applied to properly prepared surfaces of any material.



Advantages:

- High durability
- For exterior and interior use
- Forms a hard, non-cracking finish

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

30.000 ± 2.500 cps
(BROOKFIELD sp.7/50rpm, 25°C)

Density

1,58 ± 0,03 Kg / L (ISO 2811)
for the white

COVERAGE



Per coat

1-1,5 m²/Kg

PACKAGING

White	5 kg	15 kg
-------	------	-------

FINISH

Mat	Satin	Gloss
✓		
Mat Finish		

DILUTION



Water

0-10 %

DRYING TIME



Touch dry

20-30 min

COLOURS

White.
Other shades
may be
produced
using VITEX's
basic colours



COLOR CARDS - FANDECKS



EXTERIOR USE

APPLICATION

APPLICATION FIELD

For properly prepared surfaces of any material.

PREPARATION



Surfaces should be smooth, clean and dry, free from grease, dust, loose or flaking paint.



To fill any cracks or holes use Acrylic Putty.



New surfaces made of plaster, concrete, cement, plasterboard, or **surfaces previously covered with water paints or distempers** (i.e. limewash or ceiling white) should be primed with Durovit or Acrylan Unco.



STEPS

1

Stir well before use. For the final coat, Relief is applied without dilution. In case a thinner textured pattern is desired, dilute 5-10% with water.

2

The final coat is applied with a common roller. Before the coating dries, a special roller is used to produce the desired textured pattern.

TIPS

- Application at 5-35°C and <70% RH. Don't apply if there is a risk of rain/frost in the next 48 hours.
- The coating obtains its final hardness about one week later, depending on atmospheric conditions
- It can be redecorated with any VITEX acrylic or emulsion paint, after the

- surface has been cleaned.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the container and

- store it for future use.
- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Interior matt walls and ceilings (Gloss≤25@60°)" VOC content limit **30 g/L**. Maximum VOC content **14 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

