

SILVER

Aluminium Paint For Metal Surfaces

Aluminium paint suitable for the protection of metal surfaces such as stovepipes, chimneys, heaters, barbecues etc. It is resistant to high temperatures (up to 200°C), adverse weather conditions and daylight.



Advantages::

- Suitable for exhausts, fireplaces, chimneys, heaters, barbecues and industrial applications

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Density

0,95 ± 0,02 Kg / L (ISO 2811)

DILUTION



Undiluted

Ready for use

COLOURS

Silver



COVERAGE



One coat

12-14 m²/L

Two coats

6-7 m²/L

DRYING TIME



Touch dry

2-3 h

Recoat

24 h

PACKAGING

Silver

180mL

375mL

750 mL



SPECIAL USES

APPLICATION

APPLICATION FIELD

For painting and protection of metal surfaces like stovepipes, chimneys, heaters, barbecues etc.

PREPARATION



Surfaces should be cleaned with Brush Solvent T300, be smooth and dry, free from dust, grease or rust and sanded.



STEPS

1 Stir well before use.

2 Apply the first coat by brush or roller, without dilution and without primer.

3 Recoat, if desired, after 24 hours.

TIPS

- Application at 5-35°C and <80% RH. For exterior use, do not apply if there is a risk of rain/frost in the next 48 hours.
- After application, 24 hours should elapse before warming the painted surface.

- Clean rollers and brushes with Brush Solvent T300 and then with soapy water or detergent.
- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the

- container and store it for future use.
- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"One-pack performance coatings". VOC content limit **500 g/L**. Maximum VOC content **499 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

ISO 9001
14001
CERTIFIED 45001

