

TEAK OIL

Wood Penetration Oil

Mixture of modified natural oils combined with wax. It can be used to refresh and preserve wooden surfaces like teak, oregon, rosewood, mahogany etc. as well as for all bare woods. It is suitable for interior and exterior use. It penetrates deeply through the wood pores preventing the penetration of water and enhances its natural beauty. Refreshes, preserves and protects the wood from intense sunlight and moisture.



Advantages:

- Penetration oil from mixture of modified natural oils enriched with wax
- Refreshes, preserves and protects the wood from intense sunlight and moisture

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

15 - 30 sec (FORD CUP#4, 25° C)

Density

0,87 ± 0,02 Kg / L (ISO 2811)

FINISH

Natural

Satin

Gloss



Natural finish

DILUTION




Undiluted

Ready for use

COLOURS

Colorless




COVERAGE



One coat

12-16 m²/L



Two coats

6-8 m²/L

DRYING TIME



Touch dry

2-3 h

Recoat

48 h

PACKAGING

Colorless

750 mL



WOOD PROTECTION

APPLICATION

APPLICATION FIELD

For interior and exterior wooden surfaces.

PREPARATION



Surfaces should be smooth, clean, dry, free from grease, rosins or old varnishes.



In case the surface has old varnishes, rub well with sandpaper and then apply Teak Oil.



STEPS

1 Stir well before use.

2 Apply one coat by brush or piece of cloth without dilution. Wipe excess material after 5 minutes with a dry cloth.

3 Apply a second coat for tough wood or when wood is exposed to adverse weather conditions after 48 hours.

TIPS

- Application at 5-35°C and <80% RH and wood moisture should not exceed 18%.
- Clean brushes with Brush Solvent T300 and then with soapy water or detergent.

- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the container and store it for future use.

- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Binding primers", VOC content limit **750 g/L**. Maximum VOC content **450 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

ISO 9001
14001
CERTIFIED 45001

