

VELATURA

Alkyd-Based Primer For Enamel Paints

White, mat, solvent-based alkyd primer. It provides a perfect substrate for enamels, especially when applied to wooden surfaces. Produces an excellent surface for coating with enamels paints (Verolac, Platinum PU, Aquavit Eco). It offers hiding power and whiteness, while at the same time it combines good brushability, excellent levelling properties, easy sanding and resistance to sagging.



Advantages:

- Ideal for exterior and interior wooden surfaces
- Excellent hiding power and levelling properties
- Excellent brushability
- Recoatable with water or solvent based enamel paints

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

95 ± 10 KU (ASTM D 562, 25°C)

Density

1,48 ± 0,02 Kg / L (ISO 2811)

APPLICATION

For interior and exterior use on masonry and wooden surfaces.

COLOURS

White



COVERAGE



One coat

16-18 m²/L

Two coats

8-9 m²/L

DILUTION



Up to 3%

- For brushing with Brush Solvent T300
- For spraying with Spray Gun Solvent T350

DRYING TIME



Touch dry

2-3 h

For top coat application

16-18 h

PACKAGING

White	375 mL	750 mL	2.5 L	5 L
-------	--------	--------	-------	-----



SURFACE PREPARATION

APPLICATION

PREPARATION



Surfaces should be smooth, clean and dry, free from grease, dust, loose or flaking paint.

On new wooden surfaces scrape off the knots and then apply wood preservative Diaxyl Extra for protection against fungi and insects.



To fill any cracks or holes use Acrylic Putty. Wet sanding is recommended for the surface preparation.



STEPS OF APPLICATION

1

Dilute up to 3% for brushing with brush solvent T300 or for spraying with spray gun solvent T350 and stir well before use.

2

Apply one or two coats by brush, roller or spray gun.

TOP COAT APPLICATION



After 16-18 hours the surface is sanded using a suitable sandpaper. Wipe surface to clean off loose dust particles and apply:

- Acrylic water-based enamel paint Aquavit PU Eco or
- solvent-based enamel paint Platinum PU



TIPS

- Application at 5-35°C and <80% RH. For exterior use, don't apply if there is a risk of rain/frost in the next 48 hours.
- Clean rollers, brushes with Brush Solvent T-300 and then with soapy water or detergent. Use Spray Gun

Solvent T-350 to clean spray guns.

- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the container and store it for future

use.

- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Primers" VOC content limit **350 g/L**.
Maximum VOC content **348 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

ISO 9001
14001
CERTIFIED 45001

