

VISTA DISTEMPER PAINT

Distemper Paint

Distemper (ceiling white) water-based paint for interior use. It is suitable for ceilings of bathrooms and kitchens, staircases, storehouses and generally where washing is not needed. It provides great hiding power, good spreading rate and superior whiteness, while at the same time allows surfaces to “breathe”.



Advantages:

- Excellent whiteness
- Ideal for stairwells, warehouses and ceilings
- Allows surfaces to “breathe”

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS

Viscosity

110 ± 10 KU (ASTM D 562, 25°C)




Density

1,57 ± 0,02 Kg / L (ISO 2811)
for white

Gloss

< 5 units @ 60° (ISO 2813)

COVERAGE



One coat

10-12 m²/L



Two coats

5-6 m²/L

FINISH

Mat	Satin	Gloss
✓		

Mat Finish

DILUTION



Water

10-20 %

COLOURS

White



DRYING TIME



Touch dry

30-60 min

Recoat

3-4 h

PACKAGING

White	3 L	9 L	15 L
-------	-----	-----	------



INTERIOR USE

APPLICATION

APPLICATION FIELD

For interiors, such as kitchen and bathroom ceilings, stairwells, warehouses and generally where no washing of surfaces is required.

PREPARATION



Surfaces should be clean, dry and smooth, free from dust, grease, loose or flaking paint.

STEPS

1 Dilute 10-20% with water and stir well before use.

2 Apply the first coat by brush, roller or airless spray gun.

3 Recoat after 3-4 hours.

TIPS

- Application at 5-35°C and <80% RH.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
- Minimize paint wastage by estimating

- how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the container and store it for future use.
- Do not dispose of liquid waste into

ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Interior matt walls and ceilings (Gloss≤25@60°)" VOC content limit **30 g/L**. Maximum VOC content **14 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Τα δοχεία πρέπει να διατηρούνται κλειστά σε σκιερό μέρος μακριά από την ηλιακή ακτινοβολία.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

ISO 9001
14001
CERTIFIED 45001

