

VISTA

General use emulsion paint for interior use

Mat emulsion paint for general interior use. It has great spreading rate and hiding power. With easy application and levelling properties it provides with a smooth mat finish. It is suitable for walls, ceilings, storage units and areas that need frequent painting.



Advantages:

- Great spreading rate and hiding power
- Easy application and levelling

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

110 ± 10 KU (ASTM D 562, 25°C)


Density

1,59 ± 0,02 Kg / L (ISO 2811)
for white

Gloss

< 5 units @ 85° (ISO 2813)

COVERAGE



One coat

10-12 m²/L



Two coats

5-6 m²/L

PACKAGING

| | | | |
|-------|-----|-----|------|
| White | 3 L | 9 L | 15 L |
| Bases | 3 L | 9 L | |

FINISH

| | | |
|-----|------------|-------|
| Mat | Satin | Gloss |
| ✓ | Mat Finish | |

DILUTION



Water

Up to 10%

DRYING TIME



Touch dry

30-60 min

Recoat

3-4 h

COLOURS

1500 +

White and unlimited number of shades through Vitex Coloring System



COLOR CARDS - FANDECKS:



APPLICATION

APPLICATION FIELD

Interior new surfaces made of concrete, plaster, brick, gypsum boards or old painted surfaces

Ideal for:

- Areas for professional use/ Commercial projects
- Frequent painting /freshening up

PREPARATION



Surfaces should be smooth, clean and dry, free from grease, dust, loose or flaking paint. Vista is directly applied on already painted surfaces as long as the old paint is sound. To fill any cracks or holes use Acrylic Putty or Visto.



Old surfaces previously covered with water paints or distempers (lime wash or ceiling white) should be primed with Acrylan Unco Eco or Durovit.



New surfaces made of plaster, concrete, cement, plasterboard, etc. should be first primed with 100% Acrylic Primer or Acrylan Unco Eco.



Surfaces stained from smoke, graffiti, coffee or any other kind of stain should first be primed with Blanco Eco or Vitosin.



STEPS

1 Dilute up to 10% with water and stir well before use.

2 Apply the first coat by brush, roller or airless spray gun.

3 Recoat after 3-4 hours.

TIPS

- Application at 5-35°C and <80% RH.
- The product must be exclusively tinted through Vitex Coloring System in the recommended base.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.

- Allow at least 3 weeks before cleaning and washing newly painted surfaces with Vista. Wash gently with water using a soft sponge. In case of tough stains, use a mild colourless detergent or soapy water.
- Minimize paint wastage by estimating how much paint you will need.

- Recover unused paint for re-use.
- After paint application, seal the container and store it for future use.
- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Interior matt walls and ceilings (Gloss≤25@60°)" VOC content limit **30 g/L**. Maximum VOC content **29 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

ISO 9001
14001
CERTIFIED 45001

