

# VITEX KITCHEN and BATH

## Emulsion paint for fungi protection for interior use

Emulsion paint suitable for the painting of interior surfaces in areas with high moisture and vapour condensation such as kitchens, bathrooms, ceilings and basements. Due to its special formulation prevents the growth of fungi (such as mold e.t.c) in the paint film according to standard EN 15457. It provides great hiding power, high spreading rate and superior whiteness. It has very good levelling properties and produces a smooth, flat surface. It can be applied to properly prepared surfaces of any material.



Anti fungi paint

### Advantages:

- Fungi protection
- Great spreading rate and hiding power

## PRODUCT FEATURES

### TECHNICAL CHARACTERISTICS

#### Viscosity

110 ± 10 KU (ASTM D 562, 25°C)




#### Density

1,59 ± 0,02 Kg / L (ISO 2811) for white

#### Gloss

< 5 units @ 85° (ISO 2813)

### COVERAGE



#### One coat

12-14 m<sup>2</sup>/L



#### Two coats

6-7 m<sup>2</sup>/L

### PACKAGING

White	750 mL	3 L	9 L
Bases	1 L	3 L	

### FINISH

Mat	Satin	Gloss
✓		

Mat Finish

### DILUTION



#### Water

0-10%

### DRYING TIME



#### Touch dry

30-60 min

#### Recoat

3-4 h

### COLOURS

# 1500 +

White and unlimited number of shades through Vitex Coloring System



### COLOR CARDS - FANDECKS:



## APPLICATION

### APPLICATION FIELD

Interior new surfaces made of concrete, plaster, brick, gypsum boards or old painted surfaces.

Ideal for:

- Areas with high humidity and vapors such as, kitchens, bathrooms and basements

### PREPARATION



**Surfaces should be** smooth, clean and dry, free from grease, dust, loose or flaking paint. Vitex Kitchen & Bath is directly applied on already painted surfaces as long as the old paint is sound. **To fill any cracks or holes** use Acrylic Putty or Visto.



**Surfaces with mold residues, fungi and stains** must be first cleaned with Kitchen & Bath Cleaner.

**Old surfaces** previously covered with water paints or distempers (lime wash or ceiling white) should be primed with Acrylan Unco Eco or Durovit.



**New surfaces** made of plaster, concrete, cement, plasterboard, etc. should be first primed with 100% Acrylic Primer or Acrylan Unco Eco.

**Surfaces stained** from smoke, graffiti, coffee or any other kind of stain should first be primed with Blanco Eco or Vitosin.



### STEPS

**1** Dilute up to 10% with water and stir well before use.

**2** Apply the first coat by brush, roller or airless spray gun.

**3** Recoat after 3-4 hours.

### TIPS

- Application at 5-35°C and <80% RH.
- The product must be exclusively tinted through Vitex Coloring System in the recommended base.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.

- Allow at least 3 weeks before cleaning and washing newly painted surfaces with Vitex Kitchen & Bath. Wash gently with water using a soft sponge. In case of tough stains, use a mild colourless detergent or soapy water.
- Minimize paint wastage by estimating how

much paint you will need.

- Recover unused paint for re-use. After paint application, seal the container and store it for future use.
- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

## ADDITIONAL INFORMATION

### VOCs (Volatile Organic Compounds)



"Interior matt walls and ceilings (Gloss≤25@60°)" VOC content limit **30 g/L**. Maximum VOC content **29 g/L** VOCs (ready for use product).

### PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

### STORAGE



**5°C-38°C**  
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

**+30.210.5589.400**  
TECHNICAL SUPPORT

**ISO 9001**  
**14001**  
CERTIFIED 45001

