

# VITO CONCRETE PAINT

## Water Concrete Paint

Textured coating based on a vinyl copolymer. It exhibits great hiding power and exceptional resistance to moisture and adverse weather conditions. It has very good levelling properties and forms a hard, non-cracking finish. It can be applied to properly prepared surfaces of any material.



### Advantages:

- High durability
- For exterior and interior use
- Forms a hard, non-cracking finish

## PRODUCT FEATURES

### TECHNICAL CHARACTERISTICS



#### Viscosity

110 ± 10 KU (ASTM D 562, 25°C)

#### Density

1,47 ± 0,02 Kg / L (ISO 2811)

#### Gloss


< 5 units @ 60° (ISO 2813)

### FINISH

Mat	Satin	Gloss
✓		
Mat Finish		

### COLOURS

Available in anthracite shade 985.



### COVERAGE



#### One coat

10-12 m<sup>2</sup>/L

#### Two coats

5-6 m<sup>2</sup>/L

### DILUTION



#### Water

8-10 %

### DRYING TIME



#### Touch dry

30-60 min

#### Recoat

3-4 h

### PACKAGING

Anthracite	750 mL	3 L	9 L
------------	--------	-----	-----



# EXTERIOR USE

## APPLICATION

### APPLICATION FIELD

For any cement surface.

### PREPARATION



**Surfaces should be** smooth, clean and dry, free from grease, dust, loose or flaking paint. **To fill any cracks or holes** use Acrylic Putty.



**Old surfaces** previously covered with water paints or distempers (lime wash or ceiling white) should be primed with with Acrylan Unco Eco, Durovit or Vitosin.



**New surfaces** made of plaster, concrete, cement, plasterboard, etc. should be first primed with Acrylan Unco Eco.



### STEPS

- 1 Dilute 8-10% with water and stir well before use.
- 2 Apply the first coat by brush, roller or airless spray gun.
- 3 Recoat after 3-4 hours.

### TIPS

- Application at 5-35°C and <70% RH. Don't apply if there is a risk of rain/ frost in the next 48 hours.
- Allow new concrete surfaces to cure a minimum of 30 days prior to paint application.
- Allow at least 3 weeks before cleaning and washing newly painted surfaces

- with Vito Concrete Paint. Wash gently with water using a soft sponge. In case of tough stains, use a mild colourless detergent or soapy water.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
  - Minimize paint wastage by estimating

- how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the container and store it for future use.
  - Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

## ADDITIONAL INFORMATION

### VOCs (Volatile Organic Compounds)



"Exterior walls of mineral substrate". VOC content limit **40 g/L**. Maximum VOC content **39 g/L** VOCs (ready for use product).

### PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

### STORAGE



**5°C-38°C**  
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

**+30.210.5589.400**  
TECHNICAL SUPPORT

**ISO 9001**  
**14001**  
CERTIFIED 45001

