

WOODEN FLOOR PRIMER

Water based one component transparent primer for wooden floors

Water based one component transparent acrylic floor primer. It is suitable for the preparation and filling of wooden surfaces before applying the final varnish. It has excellent adhesion, waterproofs and hardens the wood and dries quickly. It is applied and sanded easily giving smooth surface.



Advantages:

- One component transparent primer for preparation and filling of wooden surfaces before the application of the top coat
- Easy application on interior parquet, wooden floors and stairs from old and new wood

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

15-30 sec (FORD CUP#4, 25° C)

Density

1,04 ± 0,02 Kg / L (ISO 2811)

APPLICATION FIELD


For interior parquet, wooden floors and stairs.

COLOURS

Colorless



COVERAGE



One coat

8-10 m²/L



Two coats

4-5 m²/L

DILUTION



Water

5 %

DRYING TIME

Touch dry

1-2 h



Recoat

4-6 h

Top coat application

18-20 h

PACKAGING

Colorless

1 L

2.5 L



WOOD PROTECTION

APPLICATION

PREPARATION



Surfaces should be dry, clean, free from dust, waxes, oils and old floors well abraded.

STEPS OF APPLICATION

- 1 Dilute 5% with water and stir well before use.
- 2 Apply the first coat by brush or roller.
- 3 Recoat after 4-6 hours.

TOP COAT APPLICATION



After 18-20 hours the surface is rubbed using a suitable sandpaper. Wipe surface to clean off loose dust particles and apply Wooden Floor Varnish.



TIPS

- Application at 5-35°C and <80% RH and wood moisture should not exceed 18%.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the container and store it for future use.
- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"One-pack performance coatings". VOC content limit **140 g/L**. Maximum VOC content **135 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

