



# VITEX S.A.

## WASH PRIMER B' COMP.

Revision nr.10  
Dated 09/03/2023  
Printed on 01/09/2023  
Page n. 1 / 13  
Replaced revision:9 (Dated 07/04/2022)

EN

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name **WASH PRIMER B' COMP.**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Anticorrosive solventbased primer.**

#### 1.3. Details of the supplier of the safety data sheet

Name **VITEX S.A.**  
Full address **IMEROS TOPOS**  
District and Country **19300 ASPROPYRGOS (ATTIKI)**  
**GREECE**  
Tel. **(0030) 2105589400**  
Fax **(0030) 2105597859**

e-mail address of the competent person responsible for the Safety Data Sheet **vitexlab@vitex.gr**

Supplier: **VITEX S.A**

#### 1.4. Emergency telephone number

For urgent inquiries refer to **(0030) 2105589400**  
**(0030) 2107793777**

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

##### Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Acute toxicity, category 4	H312	Harmful in contact with skin.
Acute toxicity, category 4	H332	Harmful if inhaled.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Skin sensitization, category 1B	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





# VITEX S.A.

## WASH PRIMER B' COMP.

Revision nr.10  
Dated 09/03/2023  
Printed on 01/09/2023  
Page n. 2 / 13  
Replaced revision:9 (Dated 07/04/2022)

EN

### SECTION 2. Hazards identification ... / >>

Signal words: Danger

Hazard statements:

**H225** Highly flammable liquid and vapour.  
**H312** Harmful in contact with skin.  
**H332** Harmful if inhaled.  
**H304** May be fatal if swallowed and enters airways.  
**H373** May cause damage to organs through prolonged or repeated exposure.  
**H318** Causes serious eye damage.  
**H315** Causes skin irritation.  
**H335** May cause respiratory irritation.  
**H317** May cause an allergic skin reaction.  
**H412** Harmful to aquatic life with long lasting effects.  
**EUH208** Contains: Triethylenetetramine  
May produce an allergic reaction.

Precautionary statements:

**P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
**P501** Dispose of contents / container in accordance with local and national regulations.  
**P102** Keep out of reach of children.  
**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P260** Do not breathe dust / fume / gas / mist / vapours / spray.  
**P331** Do NOT induce vomiting.  
**P101** If medical advice is needed, have product container or label at hand.  
**P271** Use only outdoors or in a well-ventilated area.  
**P280** Wear protective gloves / protective clothing / eye protection / face protection.  
**P301+P310** IF SWALLOWED: Immediately call a POISON CENTER / doctor / . . .  
**P405** Store locked up.

**Contains:** Reaction mass of ethylbenzene and m-xylene and p-xylene  
FATTY ACIDS, C18-UNSAT., DIMERS, POLYMERS WITH TRIETHYLENETETRAMINE  
Triethylenetetramine

VOC (Directive 2004/42/EC) :

Two - pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition : 490,00

Limit value: 500,00

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

### SECTION 3. Composition/information on ingredients

#### 3.2. Mixtures

Contains:

Identification **x = Conc. %** **Classification (EC) 1272/2008 (CLP)**

**Reaction mass of ethylbenzene and m-xylene and p-xylene**

**INDEX**  $65 \leq x < 75$  **Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 3 H412, Classification note according to Annex VI to the CLP Regulation: C**  
**STA Dermal: 1100 mg/kg, LC50 Inhalation vapours: >10 mg/l/4h**

EC 905-562-9

CAS

REACH Reg. 01-2119488216-32-XXXX

**FATTY ACIDS, C18-UNSAT., DIMERS, POLYMERS WITH TRIETHYLENETETRAMINE**

**INDEX**  $15 \leq x < 25$  **Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1B H317, Aquatic Chronic 2 H411**

EC 500-290-3



# VITEX S.A.

## WASH PRIMER B' COMP.

Revision nr.10  
Dated 09/03/2023  
Printed on 01/09/2023  
Page n. 3 / 13  
Replaced revision:9 (Dated 07/04/2022)

EN

### SECTION 3. Composition/information on ingredients ... / >>

CAS 103758-99-2  
REACH Reg. 01-2119978243-32-xxxx  
**XYLENE (MIXTURE OF ISOMERS)**  
INDEX 601-022-00-9  $3 \leq x < 6$

**Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C STA Dermal: 1100 mg/kg, LC50 Inhalation vapours: >10 mg/l/4h**

EC 215-535-7  
CAS 1330-20-7  
REACH Reg. 01-2119488216-XXXX

#### ETHYLBENZENE

INDEX 601-023-00-4  $1,5 \leq x < 2,5$

EC 202-849-4

CAS 100-41-4

#### Triethylenetetramine

INDEX  $0,5 \leq x < 1$

**Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373 LC50 Inhalation vapours: 17,2 mg/l/4h**

EC 292-588-2

CAS 90640-67-8

REACH Reg. 01-2119487919-13-xxxx

**Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Chronic 3 H412 STA Oral: 500 mg/kg, STA Dermal: 1100 mg/kg**

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### SECTION 4. First aid measures

#### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

**INGESTION:** Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

**INHALATION:** Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

### SECTION 5. Firefighting measures

#### 5.1. Extinguishing media

##### SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

##### UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

#### 5.2. Special hazards arising from the substance or mixture

##### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

#### 5.3. Advice for firefighters

##### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

##### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).



# VITEX S.A.

## WASH PRIMER B' COMP.

Revision nr.10  
Dated 09/03/2023  
Printed on 01/09/2023  
Page n. 4 / 13  
Replaced revision:9 (Dated 07/04/2022)

EN

### SECTION 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

### SECTION 7. Handling and storage

#### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

### SECTION 8. Exposure controls/personal protection

#### 8.1. Control parameters

Regulatory References:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről



# VITEX S.A.

## WASH PRIMER B' COMP.

Revision nr.10  
Dated 09/03/2023  
Printed on 01/09/2023  
Page n. 5 / 13  
Replaced revision:9 (Dated 07/04/2022)

EN

### SECTION 8. Exposure controls/personal protection ... / >>

HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemičkim tvarima na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

### Reaction mass of ethylbenzene and m-xylene and p-xylene

#### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	221		442		SKIN
TLV	CZE	200		400		SKIN
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLEP	FRA	221	50	442	100	SKIN
TLV	GRC	435	100	650	150	SKIN
AK	HUN	221		442		SKIN
GVI/KGVI	HRV	221	50	442	100	SKIN
NPEL	SVK	221	50	442		SKIN
WEL	GBR	220	50	441	100	
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

#### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

### XYLENE (MIXTURE OF ISOMERS)

#### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	221		442		SKIN
TLV	CZE	200		400		SKIN
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLEP	FRA	221	50	442	100	SKIN
TLV	GRC	435	100	650	150	SKIN
AK	HUN	221		442		SKIN
GVI/KGVI	HRV	221	50	442	100	SKIN
NPEL	SVK	221	50	442		SKIN
WEL	GBR	220	50	441	100	
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

#### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation	174 mg/m3	174 mg/m3	VND	14,8 mg/m3	289 mg/m3	289 mg/m3	VND	77 mg/m3
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d



# VITEX S.A.

## WASH PRIMER B' COMP.

Revision nr.10  
Dated 09/03/2023  
Printed on 01/09/2023  
Page n. 6 / 13  
Replaced revision:9 (Dated 07/04/2022)

EN

### SECTION 8. Exposure controls/personal protection ... / >>

#### ETHYLBENZENE

##### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	435		545		SKIN
TLV	CZE	200	45,4	500	113,5	SKIN
AGW	DEU	88	20	176	40	SKIN
MAK	DEU	88	20	176	40	SKIN
VLEP	FRA	88,4	20	442	100	SKIN
TLV	GRC	435	100	545	125	
AK	HUN	442		884		SKIN
GVI/KGVI	HRV	442	100	884	200	SKIN
TLV	ROU	442	100	884	200	SKIN
NPEL	SVK	442	100	884	200	SKIN
WEL	GBR	441	100	552	125	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

##### Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

##### HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

##### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

##### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

##### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

##### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

### SECTION 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	yellowish	
Odour	characteristic	



# VITEX S.A.

## WASH PRIMER B' COMP.

Revision nr.10  
Dated 09/03/2023  
Printed on 01/09/2023  
Page n. 7 / 13  
Replaced revision:9 (Dated 07/04/2022)

EN

### SECTION 9. Physical and chemical properties ... / >>

Melting point / freezing point	not available		
Initial boiling point	> 35 °C		
Flammability	not available		
Lower explosive limit	not available		
Upper explosive limit	not available		
Flash point	< 23 °C		
Auto-ignition temperature	not available		
Decomposition temperature	not available		
pH	not available		
Kinematic viscosity	<20,5 mm <sup>2</sup> /sec (40°C)		
Dynamic viscosity	15-30 s		Method:FORD CUP#4 Temperature: = 20 °C
Solubility	not available		
Partition coefficient: n-octanol/water	not available		
Vapour pressure	not available		
Density and/or relative density	0,86-0,90	kg/l	Method:ISO 2811
Relative vapour density	not available		
Particle characteristics	not applicable		

#### 9.2. Other information

##### 9.2.1. Information with regard to physical hazard classes

Information not available

##### 9.2.2. Other safety characteristics

Information not available

### SECTION 10. Stability and reactivity

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

##### ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

#### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

#### 10.5. Incompatible materials

Information not available

#### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

##### ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

### SECTION 11. Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

##### Information on likely routes of exposure





# VITEX S.A.

## WASH PRIMER B' COMP.

Revision nr.10  
Dated 09/03/2023  
Printed on 01/09/2023  
Page n. 8 / 13  
Replaced revision:9 (Dated 07/04/2022)

EN

### SECTION 11. Toxicological information ... / >>

#### ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesl). Is irritating for skin, conjunctiva and respiratory tract.

#### Interactive effects

Information not available

#### ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:	12,29 mg/l
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	1358,02 mg/kg

#### Reaction mass of ethylbenzene and m-xylene and p-xylene

STA (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	> 2000 mg/kg Rat
LC50 (Inhalation vapours):	> 10 mg/l/4h Rat

#### XYLENE (MIXTURE OF ISOMERS)

STA (Dermal):	1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)
LD50 (Oral):	> 2000 mg/kg Rat
LC50 (Inhalation vapours):	> 10 mg/l/4h Rat

#### ETHYLBENZENE

LD50 (Dermal):	15354 mg/kg Rabbit
LD50 (Oral):	3500 mg/kg Rat
LC50 (Inhalation vapours):	17,2 mg/l/4h Rat

#### SKIN CORROSION / IRRITATION

Causes skin irritation

#### SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

#### RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

#### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

#### ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).  
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

May cause respiratory irritation





# VITEX S.A.

## WASH PRIMER B' COMP.

Revision nr.10  
Dated 09/03/2023  
Printed on 01/09/2023  
Page n. 9 / 13  
Replaced revision:9 (Dated 07/04/2022)

EN

### SECTION 11. Toxicological information ... / >>

#### STOT - REPEATED EXPOSURE

May cause damage to organs

#### ASPIRATION HAZARD

Toxic for aspiration

#### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

### SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

#### 12.1. Toxicity

Reaction mass of ethylbenzene and m-xylene and p-xylene

LC50 - for Fish	> 1 mg/l/96h
EC50 - for Crustacea	> 1 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 1 mg/l/72h
Chronic NOEC for Fish	> 1 mg/l based on test data
Chronic NOEC for Crustacea	> 0,1 mg/l

XYLENE (MIXTURE OF ISOMERS)

LC50 - for Fish	> 1 mg/l/96h
EC50 - for Crustacea	> 1 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 1 mg/l/72h
Chronic NOEC for Fish	> 1 mg/l based on test data
Chronic NOEC for Crustacea	> 0,1 mg/l

#### 12.2. Persistence and degradability

Reaction mass of ethylbenzene and m-xylene and p-xylene

Rapidly degradable

XYLENE (MIXTURE OF ISOMERS)

Rapidly degradable

ETHYLBENZENE

Solubility in water 1000 - 10000 mg/l  
Rapidly degradable

#### 12.3. Bioaccumulative potential

Reaction mass of ethylbenzene and m-xylene and p-xylene

Partition coefficient: n-octanol/water 3,12

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: n-octanol/water 3,12

ETHYLBENZENE

Partition coefficient: n-octanol/water 3,6

#### 12.4. Mobility in soil

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

#### 12.6. Endocrine disrupting properties



# VITEX S.A.

## WASH PRIMER B' COMP.

Revision nr.10  
Dated 09/03/2023  
Printed on 01/09/2023  
Page n. 10 / 13  
Replaced revision:9 (Dated 07/04/2022)

EN

### SECTION 12. Ecological information ... / >>

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

### SECTION 13. Disposal considerations

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### SECTION 14. Transport information

#### 14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1263

#### 14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

#### 14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



#### 14.4. Packing group

ADR / RID, IMDG, IATA: III

#### 14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

#### 14.6. Special precautions for user

ADR / RID: HIN - Kemler: 30  
Special provision: -

Limited Quantities: 5 L

Tunnel restriction code: (D/E)

IMDG: EMS: F-E, S-E

Limited Quantities: 5 L

IATA: Cargo:

Maximum quantity: 220 L

Packaging instructions: 366

Passengers:

Maximum quantity: 60 L

Packaging instructions: 355

Special provision:

A3, A72, A192

#### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant



# VITEX S.A.

## WASH PRIMER B' COMP.

Revision nr.10  
Dated 09/03/2023  
Printed on 01/09/2023  
Page n. 11 / 13  
Replaced revision:9 (Dated 07/04/2022)

EN

### SECTION 15. Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors  
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Two - pack performance coatings.

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

### SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Skin Corr. 1B</b>	Skin corrosion, category 1B
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Skin Sens. 1B</b>	Skin sensitization, category 1B
<b>Aquatic Chronic 2</b>	Hazardous to the aquatic environment, chronic toxicity, category 2
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H302</b>	Harmful if swallowed.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H314</b>	Causes severe skin burns and eye damage.

**VITEX S.A.****WASH PRIMER B' COMP.**Revision nr.10  
Dated 09/03/2023  
Printed on 01/09/2023  
Page n. 12 / 13  
Replaced revision:9 (Dated 07/04/2022)

EN

**SECTION 16. Other information ... / >>**

<b>H318</b>	Causes serious eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H411</b>	Toxic to aquatic life with long lasting effects.
<b>H412</b>	Harmful to aquatic life with long lasting effects.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
  4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2019/521 (XII Atp. CLP)
  16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
  17. Regulation (EU) 2019/1148
  18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
  19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
  20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
  21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
  22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition



# VITEX S.A.

## WASH PRIMER B' COMP.

Revision nr.10  
Dated 09/03/2023  
Printed on 01/09/2023  
Page n. 13 / 13  
Replaced revision:9 (Dated 07/04/2022)

EN

### SECTION 16. Other information ... / >>

- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

#### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

#### Changes to previous review:

The following sections were modified:

02 / 03 / 08 / 09 / 10 / 11 / 12 / 16.