

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **EPOXY LIGHT FILLER COMP. B'**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Epoxy Filler**

1.3. Details of the supplier of the safety data sheet

Name **VITEX S.A.**
Full address **IMEROS TOPOS**
District and Country **19300 ASPROPYRGOS (ATTIKI)**
GREECE

Tel. **(0030) 2105589400**

Fax **(0030) 2105597859**

e-mail address of the competent person responsible for the Safety Data Sheet **captain@eumaria.com**

Product distribution by: **VITEX S.A**

1.4. Emergency telephone number

For urgent inquiries refer to **(0030) 2105589400**
(0030) 2107793777

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

| | | |
|--------------------------------|------|--|
| Acute toxicity, category 4 | H302 | Harmful if swallowed. |
| Acute toxicity, category 4 | H332 | Harmful if inhaled. |
| Skin corrosion, category 1B | H314 | Causes severe skin burns and eye damage. |
| Serious eye damage, category 1 | H318 | Causes serious eye damage. |
| Skin sensitization, category 1 | H317 | May cause an allergic skin reaction. |

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

| | |
|---------------|---|
| H302 | Harmful if swallowed. |
| H332 | Harmful if inhaled. |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |
| EUH208 | Contains: Triethylenetetramine May produce an allergic reaction. |



VITEX S.A.

EPOXY LIGHT FILLER COMP. B'

Revision nr.3
Dated 10/04/2020
Printed on 21/07/2020
Page n. 2 / 11
Replaced revision:2 (Dated 22/08/2019)

SECTION 2. Hazards identification ... / >>

Precautionary statements:

- P101** If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P280 Wear protective gloves / eye protection / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER / doctor / . . .
P501 Dispose of contents / container in accordance with local and national regulations.
P260 Do not breathe dust / fume / gas / mist / vapours / spray.
P405 Store locked up.

Contains: Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)-
Polyamide
Phenol, methylstyrenated

Product not intended for uses provided for by Dir. 2004/42/CE.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

| Identification | x = Conc. % | Classification 1272/2008 (CLP) |
|---|------------------------|---|
| Polyamide | | |
| CAS | 68410-23-1 24 ≤ x < 25 | Eye Dam. 1 H318 |
| EC | | |
| INDEX | | |
| Phenol, methylstyrenated | | |
| CAS | 68512-30-1 24 ≤ x < 25 | Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 3 H412 |
| EC | 270-966-8 | |
| INDEX | | |
| Reg. no. | 01-2119555274-38-XXXX | |
| Poly[oxy(methyl-1,2-ethanediyl)],a-(2-aminomethylethyl)-w-(2-aminomethylethoxy)- | | |
| CAS | 9046-10-0 24 ≤ x < 25 | Skin Corr. 1B H314, Eye Dam. 1 H318 |
| EC | | |
| INDEX | | |
| 2,4,6-tris(dimethylaminomethyl)phenol | | |
| CAS | 90-72-2 9 ≤ x < 10 | Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315 |
| EC | 202-013-9 | |
| INDEX | 603-069-00-0 | |
| Reg. no. | 01-2119560597-27-XXXX | |
| Benzyl Alcohol | | |
| CAS | 100-51-6 9 ≤ x < 10 | Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319 |
| EC | 202-859-9 | |
| INDEX | 603-057-00-5 | |
| Reg. no. | 01-2119492630-38-XXXX | |
| Triethylenetetramine | | |
| CAS | 112-24-3 0 ≤ x < 1 | Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Chronic 3 H412 |
| EC | 203-950-6 | |
| INDEX | 612-059-00-5 | |

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.



VITEX S.A.

EPOXY LIGHT FILLER COMP. B'

Revision nr.3
Dated 10/04/2020
Printed on 21/07/2020
Page n. 3 / 11
Replaced revision:2 (Dated 22/08/2019)

SECTION 4. First aid measures ... / >>

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.**INGESTION:** Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.
INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.



VITEX S.A.

EPOXY LIGHT FILLER COMP. B'

Revision nr.3
Dated 10/04/2020
Printed on 21/07/2020
Page n. 4 / 11
Replaced revision:2 (Dated 22/08/2019)

SECTION 7. Handling and storage ... / >>

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

| | | |
|-----|-----------------|---|
| BGR | България | МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА № 13 от 30 декември 2003 г (4 Септември 2018г) |
| CZE | Česká Republika | Nařízení vlády č. 246/2018 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů |

Phenol, methylstyrenated

Predicted no-effect concentration - PNEC

| | | |
|---|--------|-------|
| Normal value in fresh water | 0,014 | mg/l |
| Normal value in marine water | 0,0014 | mg/l |
| Normal value for fresh water sediment | 52,9 | mg/kg |
| Normal value for marine water sediment | 5,3 | mg/kg |
| Normal value for water, intermittent release | 0,14 | mg/l |
| Normal value of STP microorganisms | 2,4 | mg/l |
| Normal value for the food chain (secondary poisoning) | VND | |
| Normal value for the terrestrial compartment | 10,5 | mg/kg |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | | Effects on workers | | | |
|-------------------|----------------------|----------------|---------------|------------------|--------------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | VND | VND | VND | 4 mg/kg/d | VND | VND | VND | VND |
| Inhalation | VND | VND | VND | 28 mg/m3 | VND | VND | VND | 57 mg/m3 |
| Skin | VND | VND | VND | 8 mg/kg/d | VND | VND | VND | 16,4 mg/kg/d |

Benzyl Alcohol

Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|------|---------|--------|-----|------------|-----|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 5 | | | | |
| TLV | CZE | 40 | | 80 | | |

Predicted no-effect concentration - PNEC

| | | |
|---|-------|-------|
| Normal value in fresh water | 1 | mg/l |
| Normal value in marine water | 0,1 | mg/l |
| Normal value for fresh water sediment | 5,27 | mg/kg |
| Normal value for marine water sediment | 0,527 | mg/kg |
| Normal value for water, intermittent release | 2,3 | mg/l |
| Normal value of STP microorganisms | 39 | mg/l |
| Normal value for the food chain (secondary poisoning) | VND | |
| Normal value for the terrestrial compartment | 2,3 | mg/kg |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | | Effects on workers | | | |
|-------------------|----------------------|----------------|---------------|------------------|--------------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | VND | 25 mg/kg/d | VND | 5 mg/kg/d | VND | VND | VND | VND |
| Inhalation | VND | 40,55 mg/m3 | VND | 8,11 mg/m3 | VND | 450 mg/m3 | VND | 90 mg/m3 |
| Skin | VND | 28,5 mg/kg/d | VND | 5,7 mg/kg/d | VND | 47 mg/kg/d | VND | 9,5 mg/kg/d |



VITEX S.A.

EPOXY LIGHT FILLER COMP. B'

Revision nr.3
Dated 10/04/2020
Printed on 21/07/2020
Page n. 5 / 11
Replaced revision:2 (Dated 22/08/2019)

SECTION 8. Exposure controls/personal protection ... / >>

2,4,6-tris(dimethylaminomethyl)phenol

Predicted no-effect concentration - PNEC

| | | |
|---|--------|------|
| Normal value in fresh water | 0,084 | mg/l |
| Normal value in marine water | 0,0084 | mg/l |
| Normal value for fresh water sediment | VND | |
| Normal value for marine water sediment | VND | |
| Normal value for water, intermittent release | 0,84 | mg/l |
| Normal value of STP microorganisms | 0,2 | mg/l |
| Normal value for the food chain (secondary poisoning) | VND | |
| Normal value for the terrestrial compartment | VND | |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | | Effects on workers | | | |
|-------------------|----------------------|----------------|---------------|------------------|--------------------|------------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Chronic systemic | Chronic local | Chronic systemic |
| Oral | VND | VND | VND | VND | VND | VND | VND | VND |
| Inhalation | VND | VND | VND | VND | VND | VND | VND | 0,31 mg/m3 |
| Skin | VND | VND | VND | VND | VND | VND | VND | VND |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Properties | Value | Information |
|--------------------------------|----------------|-------------|
| Appearance | paste | |
| Colour | dark red | |
| Odour | characteristic | |
| Odour threshold | Not available | |
| pH | Not available | |
| Melting point / freezing point | Not available | |
| Initial boiling point | Not available | |



VITEX S.A.

EPOXY LIGHT FILLER COMP. B'

Revision nr.3
Dated 10/04/2020
Printed on 21/07/2020
Page n. 6 / 11
Replaced revision:2 (Dated 22/08/2019)

SECTION 9. Physical and chemical properties ... / >>

| | |
|--|-----------------------------------|
| Boiling range | Not available |
| Flash point | > 93 °C |
| Evaporation Rate | Not available |
| Flammability of solids and gases | Not available |
| Lower inflammability limit | Not available |
| Upper inflammability limit | Not available |
| Lower explosive limit | Not available |
| Upper explosive limit | Not available |
| Vapour pressure | Not available |
| Vapour density | Not available |
| Relative density | 0,63-0,83 |
| Solubility | Not available |
| Partition coefficient: n-octanol/water | Not available |
| Auto-ignition temperature | Not available |
| Decomposition temperature | Not available |
| Viscosity | >20,5 mm ² /sec (40°C) |
| Explosive properties | Not available |
| Oxidising properties | Not available |

9.2. Other information

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available



VITEX S.A.

EPOXY LIGHT FILLER COMP. B'

Revision nr.3
Dated 10/04/2020
Printed on 21/07/2020
Page n. 7 / 11
Replaced revision:2 (Dated 22/08/2019)

SECTION 11. Toxicological information ... / >>

ACUTE TOXICITY

LC50 (Inhalation) of the mixture: > 20 mg/l
LD50 (Oral) of the mixture: >2000 mg/kg
LD50 (Dermal) of the mixture: Not classified (no significant component)

2,4,6-tris(dimethylaminomethyl)phenol
LD50 (Oral) 1200 mg/kg Rat

Benzyl Alcohol
LD50 (Oral) 1,23 mg/kg Rat
LD50 (Dermal) 2000 mg/kg Rabbit
LC50 (Inhalation) > 4178 mg/l/4h Rat

Triethylenetetramine
LD50 (Oral) 2100 mg/kg Rat
LD50 (Dermal) 1100 mg/kg Rat

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin
May produce an allergic reaction.

Contains:
Triethylenetetramine

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: >20,5 mm²/sec (40°C)

SECTION 12. Ecological information

12.1. Toxicity

2,4,6-tris(dimethylaminomethyl)phenol
LC50 - for Fish 345 mg/l/96h QSAR



VITEX S.A.

EPOXY LIGHT FILLER COMP. B'

Revision nr.3
Dated 10/04/2020
Printed on 21/07/2020
Page n. 8 / 11
Replaced revision:2 (Dated 22/08/2019)

SECTION 12. Ecological information ... / >>

| | |
|-----------------------------------|----------------------------------|
| Triethylenetetramine | |
| LC50 - for Fish | 495 mg/l/96h Pimephales promelas |
| EC50 - for Crustacea | 31,1 mg/l/48h Daphnia magna |
| Phenol, methylstyrenated | |
| LC50 - for Fish | > 10 mg/l/96h |
| EC50 - for Crustacea | > 10 mg/l/48h |
| EC50 - for Algae / Aquatic Plants | > 10 mg/l/72h |

12.2. Persistence and degradability

2,4,6-tris(dimethylaminomethyl)phenol
NOT rapidly degradable

Benzyl Alcohol
Rapidly degradable

12.3. Bioaccumulative potential

2,4,6-tris(dimethylaminomethyl)phenol
Partition coefficient: n-octanol/water 0,77
BCF 3

Benzyl Alcohol
Partition coefficient: n-octanol/water 1,1

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 1759

14.2. UN proper shipping name

ADR / RID: CORROSIVE SOLID, N.O.S.
IMDG: CORROSIVE SOLID, N.O.S.
IATA: CORROSIVE SOLID, N.O.S.

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|--------------------------|--|
| Acute Tox. 4 | Acute toxicity, category 4 |
| Skin Corr. 1B | Skin corrosion, category 1B |
| Eye Dam. 1 | Serious eye damage, category 1 |
| Eye Irrit. 2 | Eye irritation, category 2 |
| Skin Irrit. 2 | Skin irritation, category 2 |
| Skin Sens. 1 | Skin sensitization, category 1 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment, chronic toxicity, category 3 |
| H302 | Harmful if swallowed. |
| H312 | Harmful in contact with skin. |
| H332 | Harmful if inhaled. |
| H314 | Causes severe skin burns and eye damage. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H412 | Harmful to aquatic life with long lasting effects. |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)



VITEX S.A.

EPOXY LIGHT FILLER COMP. B'

Revision nr.3
Dated 10/04/2020
Printed on 21/07/2020
Page n. 11 / 11
Replaced revision:2 (Dated 22/08/2019)

SECTION 16. Other information ... / >>

13. Regulation (EU) 2017/776 (X Atp. CLP) 14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
16. Regulation (EU) 2019/521 (XII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

03 / 08 / 11 / 14 / 15.