

# ASTRO

## Interior Paint

Water-dispersion decorative paint for interior use, such as walls, ceilings, gypsum plasterboard etc., which allows painted surfaces to “breathe”, that is permeable to water vapor. It exhibits good adhesion, ease of application with good workability and good hiding power. It is almost odorless and washable.



**Advantages:**

- For walls, ceilings, gypsum plasterboard
- Allows surfaces to “breathe”

### PRODUCT FEATURES

#### TECHNICAL CHARACTERISTICS

**Viscosity**

110 ± 10 KU (ASTM D 562, 25°C)




**Density**

1,47 ± 0,02 Kg / L (ISO 2811)

**Gloss**

< 5 units @ 60° (ISO 2813)

#### COVERAGE



**One coat**

10-13 m<sup>2</sup>/L



**Two coats**

5-7 m<sup>2</sup>/L

#### FINISH

Mat	Satin	Gloss
✓		
Mat Finish		

#### DILUTION



**Water**

Up to 5%

#### DRYING TIME



**Touch dry**


30-60 min

**Recoat**

3-4 h

#### COLOURS

White and 12 ready-made shades



#### PACKAGING

White and 12 ready-made shades

2,5 L



## APPLICATION

### APPLICATION FIELD

For interiors, such as kitchen and bathroom ceilings, stairwells, warehouses.

### PREPARATION



**Surfaces** should be clean, dry and smooth, free from dust, grease, loose or flaking paint. Astro is directly applied on already painted surfaces as long as the old paint is sound.



**To fill any cracks or holes** use Acrylic Putty or Visto.



**New surfaces** made of plaster, concrete, cement, plasterboard, etc. should be first primed with 100% Acrylic Primer.



### STEPS

- 1 Dilute up to 5% with water and stir well before use.
- 2 Apply the first coat by brush, roller or airless spray gun.
- 3 Recoat after 3-4 hours.

### TIPS

- Application at 5-35°C and <80% RH.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
- Allow at least 3 weeks before cleaning and washing newly painted surfaces

with Astro. Wash gently with water using a soft sponge.

- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the container and

store it for future use.

- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

## ADDITIONAL INFORMATION

### VOCs (Volatile Organic Compounds)



"Interior matt walls and ceilings (Gloss≤25@60°)" VOC content limit **30 g/L**. Maximum VOC content **10 g/L** VOCs (ready for use product).

### PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

### STORAGE



**5°C-38°C**  
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

**+30.210.5589.400**  
TECHNICAL SUPPORT

**ISO 9001**  
14001  
CERTIFIED 45001

