

Vi ANTI-RUST PRIMER

Anticorrosive Primer for Metal Surfaces

Primer, based on alkyd resins, with excellent anticorrosive protection. It provides the perfect substrate for enamels used on metal surfaces, presents exceptional adhesion, hiding power, elasticity and excellent leveling properties.



Advantages:

- High anticorrosive protection
- Quick drying primer

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

80 ± 5 KU (ASTM D 562, 25°C)

Density

1,54 ± 0,02 Kg / L (ISO 2811)

APPLICATION

For metal surfaces.

COLOURS

Grey,
Dark Red



COVERAGE



One coat

12-14 m²/L

Two coats

6-7 m²/L

DILUTION



Up to 5%

- For brushing with Brush Solvent T-300
- For spraying with Spray Gun Solvent T-350

DRYING TIME



Touch dry
30-60 min

For top coat application
24 h

PACKAGING

Grey, Dark Red

650 mL

2,5 L



SURFACE PREPARATION

APPLICATION

PREPARATION



Surfaces should be cleaned with Brush Solvent T-300, be smooth and dry, free from dust, grease or rust and sanded.



STEPS OF APPLICATION

1

Dilute up to 5% for brushing with brush solvent T-300 or for spraying with spray gun solvent T-350 and stir well before use.

2

Apply one coat by brush, roller or airless spray gun.

TOP COAT APPLICATION



After 24 hours the surface is sanded using a suitable sandpaper. Wipe surface to clean off loose dust particles and apply any enamel paint for metal surfaces.

Recommend:

- Acrylic water-based enamel paint Aquavit PU Eco or
- Solvent-based enamel paint Platinum PU, Vi Enamel, Verolac, Heavy Metal Silicon



TIPS

- Application at 5-35°C and <70% RH. Don't apply if there is a risk of rain/frost in the next 48 hours.
- Clean rollers, brushes with Brush Solvent T-300 and then with soapy water or detergent. Use Spray Gun

- Solvent T-350 to clean spray guns.
- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the

- container and store it for future use.
- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"One-pack performance coatings" VOC content limit **500 g/L**. Maximum VOC content **499 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C

Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

ISO 9001
14001
CERTIFIED 45001

