

MOTIVO - MIRACLE SAND

Emulsion Paint with textured finish

Water-based paint, based on specific acrylic resins, pearlescent pigments, and silica sand, formulated specially to provide an impressive textured finish on every surface. Depending on the application method and the tools to be used, it can create a unique effect. It can be applied to walls, pillars, ceilings, plasterboards with low odour during its application.



Advantages:

- Impressive textured finish for exceptional and easy styles
- Ready in 3 and painted in 97 shades

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

115 ± 10 KU (ASTM D 562, 25°C)

Density

1,30 ± 0,02 Kg / L (ISO 2811)

COVERAGE



One coat

10-12 m²/L

PACKAGING

Silver, Gold,
Titanium

1L

3L



FINISH

Mat

Satin

Textured



Textured Finish

DILUTION



Undiluted

Ready for use

DRYING TIME




Touch dry

1-2 h

COLOURS

Available in 100 uniquely deep shades through **Vitex Coloring System** from 3 bases Silver, Gold and Titanium.



COLOR CARD



APPLICATION

APPLICATION FIELD

For the decoration of walls, columns, ceilings, plasterboard.

ΠΡΟΕΡΓΑΣΙΑ



Surfaces should be clean, dry and smooth, free from dust, grease and loose or flaking paint.



To fill any cracks or holes use Acrylic Putty or Visto.



Surfaces previously covered with water paints or distempers (lime wash or ceiling white), new surfaces made of plaster, concrete, cement, plasterboard, etc. should be first primed with Motivo – primer for a better highlight of the textured metallic finish before applying MOTIVO – MIRACLE SAND.



STEPS

1

Stir well before use and periodically during application. The product is ready for use.

2

Apply in one coat with the appropriate tool to create the desired effect on the surface.

TIPS

- Application at 5-35°C and <80% RH.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
- Allow at least 3 weeks before cleaning and washing newly painted surfaces with MOTIVO - Miracle Sand.

- Wash gently with water using a soft sponge. In case of tough stains, use a mild colourless detergent or soapy water.
- Minimize paint wastage by estimating how much paint you will need.

- Recover unused paint for re-use. After paint application, seal the container and store it for future use.
- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



“Decorative effect coatings” VOC content limit **200 g/L**. Maximum VOC content **195g/L** (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777.

STORAGE



5°C-38°C

Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

