

# ENAMELO

## Acrylic Water-Based Enamel Paint

Acrylic water-based enamel paint ideal for interior surfaces made of wood. It is applied easily and gives a smooth surface without brush and/or joint marks. It exhibits great whiteness, very good hiding power, very good durability to frequent washing and very good adhesion. Low odour paint during its application because it does not contain ammonia or other dangerous substances.



### Advantages:

- Low-cost solution
- Very good hiding power and durability
- Low odour formulation

## PRODUCT FEATURES

### TECHNICAL CHARACTERISTICS

#### Viscosity

95 ± 5 KU (ASTM D 562, 25°C)



#### Density

1,22 ± 0,02 Kg / L (ISO 2811)  
for white

#### Gloss


• At 60° (ISO 2813):  
20-40 units (satin)

### COVERAGE



#### One coat

12-15 m<sup>2</sup>/L



#### Two coats

6-8 m<sup>2</sup>/L

### PACKAGING

White (Satin)	750 mL	2,25 L
Bases (Satin)	750 mL	2,25 L

### FINISH

Mat	Satin	Gloss
	✓	

### DILUTION



#### Water

5-15 %

### DRYING TIME



#### Touch dry

1-2 h

#### Recoat

6-8 h

### COLOURS

# 1500+

White and unlimited number of shades through Vitex Coloring System



### COLOR CARDS - FANDECKS



# ENAMEL PAINTS FOR WOOD

## APPLICATION

### APPLICATION FIELD

**Interior new wooden surfaces or old painted surfaces with water based paints or solvent based varnishes (such as doors, windows, cabinets, etc.).**

Suitable also for interior walls (in satin finish)

### PREPARATION



**Surfaces should be** smooth, clean and dry, free from grease or dust and sanded.



**Properly prepared new wooden surfaces** and old painted ones with alkyd paint (stoppered, filled with Acrylic Putty and sanded down to a clean, smooth surface) should be coated with Velatura Eco. Then use an appropriate abrasive paper to produce a smooth surface and remove the dust.



### STEPS

- 1** Dilute with water 5-10% (brush/roller) or 10-15% (airless spray gun) and stir well before use.
- 2** Apply the first coat by brush, roller or airless spray gun.
- 3** Recoat after 6-8 hours.

### TIPS

- Application at 5-35°C and <80% RH.
- The product must be exclusively tinted through Vitex Coloring System in the recommended base.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
- Allow at least 3 weeks before cleaning

and washing newly painted surfaces with ENAMELO. Wash gently with water using a soft sponge. In case of tough stains, use a mild colourless detergent or soapy water.

- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the container and

store it for future use.

- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

## ADDITIONAL INFORMATION

### VOCs (Volatile Organic Compounds)



"Interior/exterior trim and cladding paints for wood and metal" VOC content limit **130 g/L**. Maximum VOC content **100 g/L** VOCs (ready for use product).

### PRECAUTIONS



Please read carefully the labelling mentioned on the can before use.  
For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request.  
Poisons Control Centre Tel. : +30 210 7793 777

### STORAGE



**5°C-38°C**  
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

**+30.210.5589.400**  
TECHNICAL SUPPORT

